

450i - EtherNet/IP to 16 Form C Relay Outputs

Part: 450i | **Model:** SeaNET-450i

Sealevel SeaNET™ modules offer powerful data acquisition solutions that are perfect for a wide range of applications and environments with easy interfacing to computers, controllers, and PLCs. SeaNET modules are available in various I/O configurations. Each SeaNET model is designed for maximum flexibility and easy field wiring

The 450i provides control for a variety of low voltage, low current devices. The module's 16 channels of highly reliable SPDT Form C relay outputs are rated for up to 60VDC @ 2A. Each output offers normally-open and normally-closed contact connections via 3.5mm field removable terminal blocks.

All SeaNET modules have the same enclosure dimensions of 7.61" W X 1.375" H X 5.08" D and include the same connectors and configuration options on the side of the unit. All SeaNET devices have a power requirement of 9-30V.

Features & Specifications

450i - EtherNet/IP to 16 Form C Relay Outputs

Part: 450i | **Model:** SeaNET-450i

Features

- 16 SPDT Form C relays outputs
- DIN rail or table mount

Specifications

Number of Inputs/Outputs	0 Inputs / 16 Outputs
Outputs	16 SPDT Form C relays
Output Power	DC 30W/ AC 60 VA
Contact Voltage	60VDC max. / 50VAC max.
Contact Current	2A max.
Operate time	2ms max
Bounce Time	7ms max
Release Time	1ms max
Operating Temperature	0°C to 70°C (32°F to 158°F)
Power Requirement	9-30V
# of Ports	0/16
Dimensions	7.61” W X 1.375” H X 5.08” D