



# Low Profile PCI 8 Reed Relay Output / 8 Isolated Input Digital Interface (10-30V)

**Part:** 8012H | **Model:** DIO-16.LPCI

Optimized for sensing 24V inputs, the 8012H Low Profile PCI digital interface provides eight Reed relay outputs (SPST) and eight optically isolated inputs supporting 10-30V. Reed relays are well suited for low current applications. The relays are normally open, and close when energized. The board is MD1 Low Profile and Universal Bus (3.3V and 5V) compatible.

The 8012H is for use in Low Profile PCI slots only. Order the 8012SH if you have a standard size PCI slot. The inputs on the 8012H are rated for 10-30V. For 3-13V inputs, order the 8012.

Sealevel's SealO Classic software drivers and utilities make installation and operation easy using Microsoft Windows operating systems.

Get a jump start on your digital I/O development with The Digital I/O Handbook that will provide helpful information that you will use again and again. Check out Chapter 1 for an overview of logic principles.

## Features & Specifications

### Low Profile PCI 8 Reed Relay Output / 8 Isolated Input Digital Interface (10-30V)

**Part:** 8012H | **Model:** DIO-16.LPCI

#### Features

- Compliant with RoHS and WEEE directives
- Eight Reed relay outputs (SPST)
- Eight optically isolated inputs optimized for +24V
- Highly reliable 10VA DIP Reed relays
- MD1 Low Profile and Universal Bus (3.3V and 5V) compatible
- Power (+5V and +12V) and ground provided on connector
- SealO Classic software supports Microsoft Windows operating systems
- Software support for Linux available

#### Specifications

<b>Board Connector</b>	DB-44F
<b>Contact Current</b>	500 mA
<b>Contact Voltage</b>	60 VDC/42 VAC
<b>Digital I/O</b>	Isolated Inputs, Reed Relay Outputs
<b>Extended Temperature</b>	Call for Options
<b>Humidity Range</b>	10 – 90% Relative Humidity, Non-Condensing
<b>Input Range</b>	10-30 VDC
<b>Input Impedance</b>	3.3 kΩ
<b>Host Interface(s)</b>	PCI
<b>Number of Inputs/Outputs</b>	8 Inputs 8 Outputs
<b>Operating Temperature</b>	0°C to 70°C (32°F to 158°F)
<b>PC Bracket</b>	Low Profile
<b># of Ports</b>	8/8
<b>Power Requirement</b>	+5V @ 280mA
<b>RoHS Compliant</b>	Yes
<b>Storage Temperature</b>	-50°C to 105°C (-58°F to 221°F)