

**CIPHER LAB**  
Smarter

# 1500 series



## **1500 series scanners from CipherLab**

Bringing retail productivity and performance up to speed, the 1500 series of scanners offers powerful reliability with efficiency. Ideal for a wide range of applications from retail to healthcare and post offices, the 1500 scanner is not only advanced, but its ergonomic design also provides extreme durability – day in, day out.

# 1500 Serie



## 1500 Series Scanners from CipherLab

### Accelerate your business

Handheld scanners are much faster than human fingers. Pull the trigger and the work is done instantly: complete series, update inventories, check patient records, and record production line parts and activities. Handheld scanners accelerate work with error-free capture of critical information, keeping your company data up to date and up to the minute.

### Cut costs

CipherLab scanners are versatile, agile, and priced right for long-lasting value. Your company benefits from years of use, backed by a manufacturer honored in the industry for its innovative, reliable products and customer service. The 1500 series scanners capture data from regular to long barcodes with a choice of linear imager, 2D imager, or laser. Together with Bluetooth cordless and corded applications, the 1500 series scanners help you run business more efficiently with improved operations.

### Go where the work takes you

The 1500 series includes wireless scanners to unleash workers, so they can go where the work is and get more done, in more places. Our 1500 series Bluetooth scanners connect with the communication stand up to 90 meters (295 feet) away. Beyond that, they keep working by storing information until the scanner is back in range.

## Smart solutions with immediate payoffs

### Accelerate receiving with fast, reliable, low-cost CipherLab 1500 handheld scanners

European retail giant Valora deployed 1,100 CipherLab 1500 scanners to improve product receiving in its Swiss sales outlets.



“After performing extensive tests, it was clear that the CipherLab scanner performed much better than any of the other solutions. We had no previous experience with CipherLab and were positively surprised with its error-free scans, reliability, and the convincing value for money it offers.”

*Christian Wurger, Head of the Corporate IT Operation/ Support, Valora, Switzerland*

### Streamline tracking and delivery with wireless CipherLab Bluetooth scanners

To ensure better tracking and delivery of mail and goods, Brazil's ECT, the largest post office in Latin America, relies on the flexibility and productivity of CipherLab Bluetooth scanners.



“With the new scanners, employees can easily reach the items to scan. They can walk around outdoors and scan packages in the unloading/departing zones, allowing them to work faster and get more work done. And the database is always updated when they are back in wireless range.”

*Marcel Gomes, Complex Solutions Provider for ECT, Brazil.*

### Update stock and reply distribution requirements in real time with wireless CipherLab Bluetooth scanners

To ensure accurate CD/DVD replenishment, ASDA/Wal-Mart combines the wireless connectivity of CipherLab Bluetooth scanners and smart phones/PDAs to instantly send stocking requirements to the distribution center.



“After searching worldwide for scanners with good communication capabilities, we found CipherLab Bluetooth scanners with high-quality and reliable performance. CipherLab scanners not only provide real-time stocking updates, but also record deliveries made to the actual supermarkets, which improves the efficiency of our business operation.”

*Altat Sadique, CEO, Gane Data LTD., United Kingdom*

## Snappy scanning, speedy decoding

The 1500 series with linear imaging reader scan and decode barcodes up to 200 times per second to speed work, eliminate rescans and keep up with your fastest operation. This high speed delivered with low power consumption makes auto-sense scanning very effective.

## Wireless freedom

### Range of Operation

The 1500 series Bluetooth wireless scanners have a 90-meter line-of-sight range from the communication stand. If it's not in range, with the optional linear imager and laser scanners, the scanner's buffer memory holds up to 256 scans in reserve, ready to transmit automatically when you're back in range again. Or, use batch mode to record over 32,000 scans – that's freedom to roam widely. The 1500 Bluetooth scanner with 2D reader has a buffer memory of 10K or 4MB in batch mode.

### House of Wireless Power

CipherLab offers you the multi-shift service with the 1500 series Bluetooth scanner. Without interruption of workflow, users get to finish work more productively and efficiently.

## A Great Variety at Your Fingertips

Every business is different and has different scanning needs, which is why CipherLab have a broad range of scanners to suit any businesses whatever their needs. The 1500 series comes in a range of varieties. The linear imager scanner offers the option of reading long barcodes, for example the ones on bills, making it suitable for utility companies, banks, and collecting agencies. The option of 2D imager is good for scanning barcodes on medicine packaging or hospital equipments making them suited for pharmaceutical or hospitals.

## PC Software to Custom-Configure Scanners to Any Environment

CipherLab **ScanMaster** software provides comprehensive tools to configure any scanner, such as enabling and disabling hands-free scanning, choosing edit format and symbology types, plus more. With ScanMaster, scanners can be easily customized to fit every working environment. ScanMaster for PC is included with all CipherLab scanners. In addition, 1500 series is also supported by **CipherConnect** which is a COM-to-key utility designed for CipherLab Bluetooth scanners to work as an input device for smart devices, such as Smartphone or PDA. The software enables intensive data collection and transmission via CipherLab Bluetooth scanner to the smart device.



# SPECIFICATIONS

# 1500 series scanner

Fast and reliable



|                                        |                                                                                                                                                                                                                                                             | Linear Imager                                                                                                                                                                                                 | Laser                                                                                  | 2D Imager                                                                                                                                                                                                                                                                                                                                                                                                                                 |
|----------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Category                               | Corded                                                                                                                                                                                                                                                      | 1500, 1500WA                                                                                                                                                                                                  | 1502                                                                                   | 1504                                                                                                                                                                                                                                                                                                                                                                                                                                      |
|                                        | Bluetooth cordless                                                                                                                                                                                                                                          | 1560                                                                                                                                                                                                          | 1562                                                                                   | 1564                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| RF Communication of Bluetooth scanner  | Module                                                                                                                                                                                                                                                      | Bluetooth Class 2 (2.4 GHz) Version 2.0                                                                                                                                                                       |                                                                                        |                                                                                                                                                                                                                                                                                                                                                                                                                                           |
|                                        | Coverage                                                                                                                                                                                                                                                    | 90 m <sup>1</sup> / 295 ft. line of sight                                                                                                                                                                     |                                                                                        |                                                                                                                                                                                                                                                                                                                                                                                                                                           |
|                                        | Standard profile                                                                                                                                                                                                                                            | SPP, HID                                                                                                                                                                                                      |                                                                                        |                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Performance                            | Optical sensor                                                                                                                                                                                                                                              | 2500 pixels                                                                                                                                                                                                   | Laser                                                                                  | 752 x 480 pixels                                                                                                                                                                                                                                                                                                                                                                                                                          |
|                                        | Light source                                                                                                                                                                                                                                                | Red LED 625 nm<br>(1500WA: Red LED 618-626 nm)                                                                                                                                                                | Visible laser diode at 650 ± 15 nm                                                     | 625 ± 5 nm LEDs (2x)                                                                                                                                                                                                                                                                                                                                                                                                                      |
|                                        | Resolution                                                                                                                                                                                                                                                  | 3 mil                                                                                                                                                                                                         | 4 mil                                                                                  | 3 mil - 1D barcode / 5 mil - 2D barcode                                                                                                                                                                                                                                                                                                                                                                                                   |
|                                        | Depth of field<br>13 mil barcode                                                                                                                                                                                                                            | 0.5 to 35 cm / 0.2 to 13.8 in.<br>(1500WA: long barcode 8.2 cm,<br>8 mil- 7.5 to 14.5cm / 3 to 5.7 in.)                                                                                                       | 2 to 57 cm / 0.8 to 22.4 in.                                                           | Code 39 3 mil: 6.9 to 10.7 cm / 2.7 to 4.2 in.<br>Code 39 5 mil: 3.6 to 18.5 cm / 1.4 to 7.3 in.<br>Code 39 7.5 mil: 0 to 25.1 cm / 0 to 9.9 in.<br>UPCA 13 mil: 4 to 30.5 cm / 1.6 to 12 in.<br>Code 39 20mil: 0 to 50 cm / 0 to 19.7 in.<br>PDF417 5 mil: 2.8 to 4.5 cm / 1.1 to 1.8 in.<br>PDF417 6.67 mil: 4.8 to 17.5 cm / 1.9 to 6.9 in.<br>PDF417 10 mil: 0 to 22.9 cm / 0 to 9 in.<br>PDF417 15 mil: 0 to 29.7 cm / 0 to 11.7 in. |
|                                        | Scanning angle                                                                                                                                                                                                                                              | Pitch ± 70° Skew ± 70°                                                                                                                                                                                        | Pitch ± 65° Skew ± 50°                                                                 | Pitch ± 60° Skew ± 60°                                                                                                                                                                                                                                                                                                                                                                                                                    |
|                                        | PCS                                                                                                                                                                                                                                                         | Minimum 30%                                                                                                                                                                                                   | Minimum 45%                                                                            |                                                                                                                                                                                                                                                                                                                                                                                                                                           |
|                                        | Scan rate                                                                                                                                                                                                                                                   | 200 scans, decodes / second<br>(1500WA: 100 scans / second)                                                                                                                                                   | 100 scans / second                                                                     | 60 frames / second                                                                                                                                                                                                                                                                                                                                                                                                                        |
|                                        | Ambient illumination                                                                                                                                                                                                                                        | 100,000 lux                                                                                                                                                                                                   |                                                                                        |                                                                                                                                                                                                                                                                                                                                                                                                                                           |
|                                        | Hands-free scanning                                                                                                                                                                                                                                         | Auto-sense and continuous modes                                                                                                                                                                               | Continuous mode                                                                        | Auto-sense mode, continuous mode and presentation mode                                                                                                                                                                                                                                                                                                                                                                                    |
|                                        | Barcodes support                                                                                                                                                                                                                                            | Codabar, Code 39, Code 93, Code 128, GS1 DataBar (RSS),<br>Industrial 2 of 5, Interleave 2 of 5, ISBT-128, Italian and French Pharmacodes,<br>Matrix 2 of 5, MSI, Plessey, Telepen, UPC/EAN/GS1-128, and more |                                                                                        | 1D: All major codes <sup>2</sup><br>2D: PDF417, MicroPDF417, Composite, RSS,<br>TLC-39, Datamatrix, QR code, Micro QR code,<br>Aztec, MaxiCode<br>Postal Codes: US PostNet, US Planet,<br>UK Postal, Australian Postal,<br>Japan Postal Dutch Postal (KIX)                                                                                                                                                                                |
|                                        | Programmable features                                                                                                                                                                                                                                       | Data editing, interface selection, symbology configuration                                                                                                                                                    |                                                                                        |                                                                                                                                                                                                                                                                                                                                                                                                                                           |
|                                        | Language support                                                                                                                                                                                                                                            | US and UK English, French, Italian, Belgian, Norwegian/Swedish, Spanish, Portuguese, German, Japanese and Turkish                                                                                             |                                                                                        |                                                                                                                                                                                                                                                                                                                                                                                                                                           |
|                                        | Physical                                                                                                                                                                                                                                                    | Dimension L x W x H                                                                                                                                                                                           | 15.3 x 6.1 x 9.3 cm / 6.0 x 2.4 x 3.7 in.                                              |                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Weight<br>without cable / with battery |                                                                                                                                                                                                                                                             | 145 g / 5.1 oz.<br>(1560: 173 g / 6.1 oz.)                                                                                                                                                                    | 1502: 149 g / 5.2 oz.<br>1562: 177 g / 6.2 oz.                                         | 1504: 154 g / 5.4 oz.<br>1564: 185 g / 6.5 oz.                                                                                                                                                                                                                                                                                                                                                                                            |
| Color                                  |                                                                                                                                                                                                                                                             | Black                                                                                                                                                                                                         |                                                                                        |                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Switch                                 |                                                                                                                                                                                                                                                             | Tactile Switch                                                                                                                                                                                                |                                                                                        |                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Electrical                             | Memory<br>for Bluetooth scanner<br>reserver buffer / batch mode                                                                                                                                                                                             | 4 K / 512 K                                                                                                                                                                                                   |                                                                                        | 10 K / 4 M                                                                                                                                                                                                                                                                                                                                                                                                                                |
|                                        | Working hours<br>for Bluetooth scanner                                                                                                                                                                                                                      | 24 / 12 hours<br>depending on the CCD Sensor mode setting<br>(Always Active function disabled/ Always Active function enabled, default setting)                                                               | 24 hours<br>based on 1 scans / 5 seconds                                               | 16 hours<br>based on 1 scans / 5 seconds                                                                                                                                                                                                                                                                                                                                                                                                  |
|                                        | Voltage                                                                                                                                                                                                                                                     | +5 V ± 10% / 3.7 V 800 mAh Li-ion battery                                                                                                                                                                     |                                                                                        |                                                                                                                                                                                                                                                                                                                                                                                                                                           |
|                                        | Power consumption <sup>3</sup><br>Standby / Operating                                                                                                                                                                                                       | 50 mA / 265 mA<br>(1560: 45 mA / 270 mA)                                                                                                                                                                      | 1502: 35 mA / 210 mA<br>1562: 25 mA / 210 mA                                           | 1504: 30 mA / 280 mA<br>1564: 35 mA / 230 mA                                                                                                                                                                                                                                                                                                                                                                                              |
| User Environment                       | Temperature                                                                                                                                                                                                                                                 | Operating: 0°C to 50°C / 32°F to 122°F Storage: -20°C to 60°C / -4°F to 140°F                                                                                                                                 |                                                                                        |                                                                                                                                                                                                                                                                                                                                                                                                                                           |
|                                        | Humidity                                                                                                                                                                                                                                                    | Operating: 10% to 90% Storage: 5% to 95%                                                                                                                                                                      |                                                                                        |                                                                                                                                                                                                                                                                                                                                                                                                                                           |
|                                        | Impact resistance                                                                                                                                                                                                                                           | 1.5 m (4.9 ft) multiple drops onto concrete<br>(1560: 1.2 m (3.9 ft) multiple drops onto concrete)                                                                                                            | 1.2 m (3.9 ft) multiple drops onto concrete                                            |                                                                                                                                                                                                                                                                                                                                                                                                                                           |
|                                        | Ingress protection                                                                                                                                                                                                                                          | IP30                                                                                                                                                                                                          |                                                                                        |                                                                                                                                                                                                                                                                                                                                                                                                                                           |
|                                        | Electrostatic discharge                                                                                                                                                                                                                                     | ±8 kV contact ±15 kV air                                                                                                                                                                                      |                                                                                        |                                                                                                                                                                                                                                                                                                                                                                                                                                           |
|                                        | EMC regulation                                                                                                                                                                                                                                              | 1500: BSMI, CE, C-tick, FCC, IC, MIC<br>1500WA: BSMI, CE, C-tick, FCC, IC<br>1560: BSMI, CE, C-tick, FCC, IC, KCC,<br>NCC, SRMC, TELEC                                                                        | 1502: CE, C-tick, FCC, IC<br>1562: BSMI, CE, C-tick, FCC, IC, KCC,<br>NCC, SRMC, TELEC | 1504: BSMI, CE, C-tick, FCC, IC<br>1564: BSMI, CE, C-tick, FCC, IC, NCC                                                                                                                                                                                                                                                                                                                                                                   |
| Configuration                          | Setup options include Windows-based ScanMaster software, by direct connection or printing out barcode settings                                                                                                                                              |                                                                                                                                                                                                               |                                                                                        |                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Accessories                            | USB, RS232 and keyboard wedge cables,<br>Three-way desk/wall/auto-sense stand with optional weighted base, communication stand for Bluetooth scanner<br>provides Bluetooth communication for up to 7 scanners, single battery charger for Bluetooth scanner |                                                                                                                                                                                                               |                                                                                        |                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Warranty                               | 5 years (1560: 3 years)                                                                                                                                                                                                                                     |                                                                                                                                                                                                               | 3 years (engine 1 year)                                                                |                                                                                                                                                                                                                                                                                                                                                                                                                                           |

<sup>1</sup> It is based on communication stand without weighted base. <sup>2</sup> All of the barcodes that 1500 series 1D scanners can read except French Pharmacode, Plessey, and Telepen. <sup>3</sup> The data is tested with USB interface.

© 2011 CipherLab Co., Ltd. All specifications are subject to change without notice. All rights reserved. All brand, product and service, and trademark names are the property of their registered owners.



**HEADQUARTERS**  
CipherLab Co., Ltd.  
12F, 333 Dunhua S. Rd., Sec.2  
Taipei, Taiwan 10669  
Tel +886 2 8647 1166  
Fax +886 2 8732 3300  
www.cipherlab.com

**CipherLab China**  
J Room, 4F, No.728 West Yan'an  
Road, Changning District, Shanghai  
China 200050  
Tel +86 21 3368 0288  
Fax +86 21 3368 0286

**CipherLab USA**  
2552 Summit Avenue  
Plano, Texas USA 75074  
Tel +1 469 241 9779  
Toll Free 888 300 9779  
Fax +1 469 241 0697

**CipherLab Central Europe**  
Willicher Damm 143-145  
41066 Mönchengladbach  
Germany  
Tel +49 2161 56230 0  
Fax +49 2161 56230 22