

# LK SERIES

## LK-T200 Series POS Printer

- Easy-load desktop thermal printer
- Prints at either 200mm or 300mm per second
- Paper width adjustable 50 ~ 82.5mm
- Various O/S drivers: Windows printer driver (7, XP, 2000, 2003), WEPOS, OPOS, Linux, Java POS

## LK-D30 POS Printer

- Dot Impact Printer
- Drop-in paper loading
- 5 Lines/sec high speed printing
- Two color printing
- Auto cutter



LK-T200/203 ▲



LK-D30 ▲



# LK SERIES | POS Printers

## LK-T200/203 FEATURES

- Easy-load desktop thermal printer
- Prints at either 200mm or 300mm per second
- Paper width adjustable 50 ~ 82.5mm
- Various O/S drivers

## OPTIONS

- Melody Box
- Spillproof Cover

## SPECIFICATIONS



Interface ▲



Melody Box ▲

## LK-D30 FEATURES

- Drop-in paper loading
- 5 Lines/sec high speed printing
- Two color printing
- Auto cutter
- Paper End / Cover Open / Paper Low sensors

## OPTIONS

- Black mark sensor



Interface ▲



Drop-in Paper Loading ▲

Model		LK-T200	LK-T203	LK-D30
Printing	Method	Direct Thermal		9-pin Serial Dot Impact Matrix
	Direction	N/A		Bi-directional (with logical seeking)
	Speed	200 mm/sec	300 mm/sec	5 lines/sec
	Width	72 mm (512 Dots/Line)		63.5 mm (400 Dots/Line)
	Resolution	180 DPI		160 DPI / 80 DPI
Paper	Type	Thermal Paper		Roll Paper
	Width / Thickness	500 mm ~ 82.5 mm / 0.06 mm ~ 0.09 mm		57.5 mm, 69.5 mm, 76.2 mm
	Roll Diameter / Inner Core	Max. Ø 80.00 mm / 12.5 mm ± 0.5 mm		Max. 80mm
	Copies	N/A		Original + 2 Copies
Ink Ribbon		N/A		ERC-38 Compatible (Black, Purple, Black/Red)
Reliability	TPH Life	160 km		180 Million Lines
	MCBF	60 Million Lines		120 Million Characters
Auto Cutter		1,500,000 Cuts (Guillotine)		1,000,000 Cuts (Guillotine)
Sensor		Paper End, Paper Low, Cover Open, Black Mark Sensor (Option)		Paper End, Paper Low, Cover Open
Interface		USB only, USB + Serial, USB + Parallel, USB + Ethernet		Serial, USB, Ethernet
Emulation		ESC/POS Command Compatible		TM-U200, TM-U300, iDP-3540, SP200 Command Compatible
Driver		Window Printer Driver (7, XP, 2000, 2003, VISTA), WEPOS, OPOS, Linux, JavaPOS		Window Printer Driver (7, XP, 2000, 2003, VISTA), WEPOS, OPOS, Linux, JavaPOS
Power	Type	External SMPS		External SMPS
	AC	100 ~ 240 Vac 50/60 Hz		100 ~ 240 Vac 50/60 Hz
	DC	24 Vdc / 2.5 A		24 Vdc / 2.5 A
Temperature Operation / Storage		5 ~ 40°C / -20 ~ 60°C		5 ~ 40°C / -20 ~ 60°C
Dimension		152 mm x 204 mm x 150 mm (W x D x H)		156 mm x 243 mm x 150 mm (W x D x H)
Weight		1.7 kg		2.38 kg (cutter included)
Warranty		2 Years / 3 Years with CAS Paper		2 Years / 3 Years with CAS Paper



99 Murray Hill Parkway  
 East Rutherford, NJ 07073  
 TEL: (201) 933-9002  
 FAX: (201) 933-9025  
<http://www.cas-usa.com>

Specifications are subject to change for improvement without prior notice.

