

MultiBoard G81-7000



Models may vary from the image shown

Programmable compact keyboard with built-in magnetic card reader and optional barcode decoder.

Our magnetic card reader keyboards G81-7000 offer the functions of a keyboard and magnetic card reader in one single data entry system. These keyboards are ideal for recording all data via magnetic cards and barcodes - such as in the hotel and catering business, the travel industry or in banks and insurance companies.

Key benefits

- Mechanical individual keys with membrane contact switches (FTSC technology)
- Designed for continuous usage - over 50 mill. confirmations per key
- Robust and reliable
- Programmable magnetic card reader
- Optional barcode decoder. Data is converted to "scan codes" and transmitted via the PS/2 interface (like normal key operations)
- 43 programmable keys
- OPOS and JavaPOS for Windows® and Linux, client-server architectures supported
- Efficient configuration with professional Cherry Tools Software
- Integrated memory

Magnetic Stripe Reader

- 3-track reader
- Freely-programmable header and terminator per magnetic card track
- Increased security during card processing due to the programming of extended hex codes
- Acoustic signal can be activated or deactivated and sounds when the magnetic card has been read successfully

Technical Data:

Layout (country or language):

Product dependant, see table "Models"

Housing colour:

Product dependant, see table "Models"

Key colour:

Product dependant, see table "Models"

Weight (product):

approx. 1650 g

Total weight (with packaging):

approx. 2000 g

Cable Length:

approx. 1.75 m

Storage Temperature:

-20°C to 60°C

Operating Temperature:

0°C to 50°C

Current Consumption:

typ. 35 mA

Interface:

- PS/2

Connection sockets (optional, see table "Models"):

- 9-pin SUB-D plug
- 6-pin DIN 240° socket

Product approvals:

- cURus 
- c-tick 
- CE 
- FCC 
- VDE 

System requirements:

- PS/2 connection

Delivery Volume:

- MultiBoard G81-7000
- CD-ROM with up-to-date software
- Operating instructions in hard copy

Dimensions (product):

approx. 405 x 220 x 64 mm

Packaging dimensions:

approx. 455 x 277 x 72 mm

Reliability:

- MTBF > 100,000 hours
- MCBF > 10 bill. operations

Keyboard:

- Key technology: FTSC
- Service life, standard key: > 50 million key operations

- Operation characteristics: Linear
- Inscription technology: Laser
- Inscription layout: Standard
- Number of Keys: Product dependant, see table "Models"

Magnetic Stripe Reader:

- Magnetic card tracks: Track 1, Track 2, Track 3
- Magnetic card standards: ISO 7811/-12, JIS 1/2, AAMVA, Gemini
- Magnetic card reading speed: 8 - 318 cm/s at 30 Bit/cm, 8 - 127 cm/s at 83 Bit/cm
- Magnetic card reading cycles: approx. 600,000 reading cycles
- Magnetic card swipe direction: from right to left

Barcode decoder (optional, see table "Models"):

- Hardware interface: 6-pin DIN 240° socket, 9-pin SUB-D plug
- Barcode protocols: Code 11, Code 39, Code 93, Code 128, Code 16k, Plessey, Industrial 2/5, Matrix 2/5, Codabar, Interleaved 2/5, EAN/UPC, MSI

Packaging Unit:

- Number of products in the master package: 34
- Number of master packages per pallet: 2

Warranty:

2 years

Errors, technical changes and delivery possibilities excepted.
Technical information refers only to the specifications of the products. Features may differ from the information provided.

Authorised Australian Distributor:

Goodson Imports Pty Ltd

142 Wicks Road

North Ryde NSW 2113

Offices in all main States and New Zealand

Ph: 02-8875 4544 Fax 02-8875 4588

www.goodson.com.au