



Retail



Hospitality



Ticketing



Kiosk



Dual



# Affordable & Reliable!

3 inch POS printer

## SRP-330

- 2" or 3" paper choice
- Stand-alone or wall-mount
- Dual communication interface
- Reliable printing performance



**BIXOLON®**

## HIGHLIGHTS

### 2" or 3" paper choice

This two-in-one printer is equipped with a 2" partition, in which you can instantly change whether you desire 2 or 3 inch receipt. No need for utility or dip switch changes.



### Stand-alone or wall-mount

We have designed the printer to mount directly to the wall effortlessly without any additional accessories. Use this hole to secure the printer directly to your wall for space-saving convenience. Internal fixture keeps paper in place during printing for smooth printing job every time.




### Dual communication interface

- USB V2.0 FS + Ethernet
- USB V2.0 FS + Serial
- USB V2.0 FS + Parallel



### Reliable Printing Performance

- Fast printing speed: up to 200 mm/sec
- High reliability mechanism : 1.5 million cuts auto cutter, 150 km TPH
- Outstanding printing of fonts, graphics, and barcode symbologies



## SPECIFICATIONS

### Print Characteristics

**Print Method** : Direct Thermal  
**Print Speed** : 200 mm/sec  
**Print Resolution** : 180 dpi  
**Sensor** : Paper End, Cover Open

### Media Characteristics

**Media Type** : Receipt  
**Media Width** : 80 mm  
**Media Roll Diameter** : Up to 80 mm  
**Supply Method** : Easy Paper Loading

### Physical Characteristics

**Dimensions (WxLxH)** : 153 x 195 x 145 mm (6.02 x 7.68 x 5.70 inch)  
**Weight** : 1.44 kg (3.17 lbs.)  
**Power** : EnergyStar Certified,  
External Power Adaptor 100-240V AV, 50/60Hz

**Drawer Port** : 2 ports

### Performance Characteristics

**Memory** : 64 Mbit SDRAM, 16 Mbit FlashROM  
**NV Image Memory** : 256 Kbytes (mono)  
**Receive Buffer** : 4 Kbytes  
**User Define Buffer** : 12 Kbytes  
**Interface** : Dual Interface  
Serial + USB 2.0 FS  
Parallel + USB 2.0 FS  
Ethernet + USB 2.0 FS

### Environment Characteristics

**Temperature** : Operating: 0~45°C (32~113°F)  
Storage: -20~60°C (-4~140°F)  
**Humidity** : Operating: 10 ~ 80% RH  
Storage: 10 ~ 90% RH

### Reliability

**Printer Unit** : 60 million lines  
**TPH** : 150 km  
**Auto Cutter** : 1.5 million cuts

### Software

**Emulation** : BXL / POS  
**Driver** : Windows Driver, OPOS Driver, JPOS Driver, Linux CUPS Driver,  
Mac Driver, Virtual COM USB/Ethernet Driver, Utility Program  
**SDK** : Android SDK

### Fonts / Graphics / Symbologies

**Character Size** : Font A: 12 x 24 Font B: 9 x 17 Font C: 9 x 24  
KOR, CHN, JPN: 24x24  
**Characters Per Line** : Font A: 42 Font B, C: 56 / KOR, CHN, JPN: 21  
**Character Sets** : Alphanumeric: 95  
Extended Graphics: 128 x 37 page  
International: 32

**Graphics** : Supporting user-defined fonts, graphics, formats, and logos

**Barcode Symbologies** : 1D: Coda Bar, Code39, Code93, Code128,  
EAN-8, EAN-13, ITF, UPC-A, UPC-E  
2D: PDF417, QR Code

BR-SRP-330-EN-OCT13

Copyright © 2013 BIXOLON Co., Ltd. All rights reserved.

Features and specifications are subject to change without prior notice.

**BIXOLON®**

www.bixolon.com



### BIXOLON Co., Ltd.

7~8th FL, Miraeasset Venture Tower, 685, Sampyeong-dong,  
Bundang-gu, Seongnam-si, Gyeonggi-do, 463-400, KOREA (ROK)

Tel +82 (0) 31 218 5500

Fax +82 (0) 31 218 5589

E-mail sales@bixolon.com

### BIXOLON America Inc.

3171 Fujita St Torrance,  
CA 90505, USA

Tel +1 858 764 4580

Fax +1 310 257 6869

E-mail sales@bixolonusa.com

### BIXOLON Europe GmbH

Tiefenbroicher Weg 35,  
40472 Düsseldorf, Germany

Tel +49 211 68 78 54 0

Fax +49 211 68 78 54 20

E-mail sales@bixolon.de