









Epson TM-T82II

Convenient and economical Thermal Receipt Printer with all drivers and accessories for quick and easy installation

Ideal for customers with low volume of POS transactions
Featuring Epson quality and reliability
Printing speeds of up to 200mm/second for text and graphics
Flexible coupon printing on receipts



Epson's cost effective TM-T82II thermal receipt printer is built with the reliability, usability and functionality of Epson's industry leading TM-T88 series.









Quality you can count on

The TM-T82II is the ideal choice for retailers with a low volume of POS transactions. Based on Epson's advanced printing technology, it delivers the quality and reliability that Epson is known for which ensures an easy, reliable printing solution for end users.

Fast printing with multiple options

The TM-T82ll prints both text and graphics on receipts at speeds up to 200mm/second. It also features crisp, clear printing of logos, coupons and barcodes. In addition, the TM-T82ll offers paper saving options that can reduce paper usage by up to 30%.

All-in-one-box convenience

The TM-T82II comes with everything you need in one box for quick setup and installation. The box includes manuals, drivers, utilities, cables, external power supply and easy-to-use software tools to speed set-up and installation. In addition, the TM-T82II is available with USB + Serial, USB + Parallel or USB + Ethernet only interfaces.

Easy to use. Easy to maintain

The TM-T82II comes with multiple ease-of-use features from drop-in paper loading and auto cutter to status LEDs and more. And it also offers optional

printer placements including horizontal or upright for front receipt dispensing or vertical wall placement using a special hanging bracket.

ENERGY STAR qualified

Epson's TM-T82II is ENERGY STAR® qualified and RoHS compliant and features low power consumption to reduce costs.

Backed by the leader

The TM-T82II is backed by Epson's industryleading service and support programs and comes with a two-year return to base warranty.

Epson TM-T8211 Specifications

Print method	Thermal line printing
Print fonts (True type)	Font A 12(W) x 24(H) mm Font B 9(W) x 17(H) mm
Column Capacity	Standard: Paper width 80mm: 48/64; Paper width 58mm: 35/46 42 Column Mode: Paper width 80mm: 42/60; Paper width 58mm: 42/31
Character size (mm)	Font A: 1.25 (W) ×3 (H), Font B: 0.88 (W) ×2.13 (H)
Character set	95 Alphanumeric, 18sets International, 128 × 43 Extended Graphics Bar code : UPC-A, UPC-E, JAN13(EAN13), JAN8(EAN), CODE39, ITF, CODABAR(NW-7), CODE93, CODE128, GS1-128, GS1 DataBar Two-dimensional code : PDF417, QRCode, MaxiCode, Two-dimensional GS1 DataBar, Composite Symbology
Character per inch	Font A: 16.9 cpi, Font B: 22.6 cpi
Interfaces	USB + Serial, USB + Parallel, USB + Ethernet
Receive data buffer	4 KB or 45 bytes
Print speed	Max. 200 mm/sec
Resolution	203 dpi × 203 dpi
Paper dimensions (mm)	79.5 ± 0.5 (W)×dia. $83.0, 57.5 \pm 0.5$ (W)×dia. 83.0
Power	24 VDC ± 7%
Power consumption	Operating: Approx. 1.8 A (Mean / Print ratio 18% with print pattern) Standby: Approx. 0.1 A (Mean)

EDCON	AUSTRALIA	
ELOOIN	AUSTRALIA	

3 Talavera Road North Ryde NSW 2113 1300 361 054 www.epson.com.au

EPSON NEW ZEALAND

Level 2 7-9 Fanshawe Street Auckland, 1010 0800 237 766 www.epson.co.nz

Power supply	External power supply (Model: PS-180) included
Printer mechanism life	15 million lines (printing + paper feeding)
Auto cutter life	1.5 million cuts
MTBF	360,000 hours
MCBF	60,000,000 lines
EMI and safety standards	Oceania EMI AS/NZS CSPR22 Class A
Standard accessories	Roll paper × 1 roll (for checking the initial movement of the printer), CD-ROM (Drivers, Utility software, Manuals), Setup guide, Power button cover, Waterproof power button cover, Wall hanging bracket, Screws for wall hanging bracket, Rubber feet for vertical installation, Control panel sheet for vertical installation, 58-mm width paper guide, External power supply (Model: PS-180), AC cable (May not be included depending on the printer model)
Overall dimensions	140mm (W) x 199mm (D) x 146mm (H)
Weight	1.7kg
Config Builds	
C31CD52342	TM-T82II-342 USB + Serial

TM-T82ll-344 USB + Parellel

TM-T82II-347 USB + Ethernet

ABN 91 002 625 783

C31CD52344

C31CD52347



