

Dell Compatible 407-BBRJ-FL Quick Spec:

Part Number: 407-BBRJ-FL
407-BBRJ-FL-EXT
407-BBRJ-FL-IND

Form Factor: SFP+
TX Wavelength: 850nm
Reach: 300m
Cable Type: MMF
Rate Category: 10GBase
Interface Type: SR
DDM: Yes
Connector Type: Dual-LC
Temperature: Commercial
Power Budget: 5.1dB
TX Power Min/Max: -6.00 to -1.00
RX Power Min/Max: -11.1 to -1.00



Dell Compatible 407-BBRJ-FL Features

- Operating Data Rate up to 10.3Gbps
- Single 3.3V Power Supply and TTL Logic Interface
- Hot Pluggable
- 850nm VCSEL Transmitter
- Reach:
 - OM1 (62.5/125micron) 33m
 - OM2 (50/125micron 400 MHz*km) 82m
 - OM3 (50/125micron 2000 MHz*km) 300m
 - OM4 (50/125micron 4700) 300m
- Operating Case Temperature
 - Standard: 0°C to +70 °C
 - Extended -5°C to +85 °C
 - Industrial -40°C to +85 °C
- Compliant with MSA
- Compliant with IEEE 802.3ae 10GBASE-SR
- Digital Diagnostic Monitor Interface
- Compliant with SFF-8472
- RoHS 6 Compliant

Dell Compatible 407-BBRJ-FL Applications

- 10G Ethernet at 10.3125Gbps

Dell Compatible 407-BBRJ-FL Electrical Characteristics (Condition: Ta=TOP)

Parameter	Symbol	Min.	Typ	Max.	Unit	Notes
CML Inputs(Differential)	V _{in}	150		1200	mV p-p	AC coupled inputs
Supply Current	I _{CC}			300	mA	
Input Impedance (Differential)	Z _{in}	85	100	115	ohm	R _{in} > 100 kohm @ DC
Tx_Disable Input Voltage – Low	V _{IL}	0		0.8	V	
Tx_Disable Input Voltage – High	V _{IH}	2.0		3.45	V	
Tx_Fault Output Voltage – Low	V _{OL}	0		0.5	V	
Tx_Fault Output Voltage – High	V _{OH}	2.0		V _{cc} +0.3	V	
CML Outputs (Differential)	V _{out}	350		700	mV pp	AC coupled outputs
Output Impedance (Differential)	Z _{out}	85	100	115	ohms	
Rx_LOS Output Voltage- Low	V _{OL}	0		0.5	V	
Rx_LOS Output Voltage- High	V _{OH}	2.5			V	

Dell Compatible 407-BBRJ-FL Optical Characteristics (Condition: Ta=TOP)

TX						
Parameter		Symbol	Min	Typ	Max	Unit
Data Rate			-	10.3	-	Gb/s
50/125mm MMF				300		m
Centre wavelength		λ _c	840	850	860	nm
Output Spectral Width(RMS)		Δλ	-	-	0.45	nm
Average Output Power		P _{out}	-6	-	-1	dBm
Extinction Ratio		ER	3.0	5.0	-	dB
Output Optical Eye			IEEE 802.3-2005 Compliant			
Transmitter Dispersion Penalty		TDP			3.9	dB
Input Differential Impedance		Z _{in}	90	100	110	Ω
TX Disable	Disable		2.0		V _{cc} +0.3	V
	Enable		0		0.8	
TX Fault	Fault		2.0		V _{cc} +0.3	V
	Normal		0		0.8	
TX Disable Assert Time		t _{off}			10	us

RX					
Parameter	Symbol	Min	Typ	Max	Unit
Center Wavelength	λ_c	840	850	860	nm
Receive Sensitivity	P_{in}	-	-	-11.1	dBm
Maximum Input Power	P_{MAX}	-1			dBm
Signal Detect Threshold-Assertion:	SD_{HIGH}	-	-	-12	dBm
Signal Detect Threshold-Deassertion:	SD_{LOW}	-25	-	-	dBm
Output Differential Impedance	P_{in}	90	100	110	Ω
Receiver Overload	P_{max}	0.5			dBm
Optical Return Loss	ORL			-12	dB
LOS	High	2.0		$V_{cc}+0.3$	V
	Low	0		0.8	

Absolute Maximum Ratings ($T_c=25^\circ\text{C}$)

Parameter	Symbol	Min	Max	Unit
Storage Temperature	T_{ST}	-40	+85	$^\circ\text{C}$
Operating Temperature (Standard)	T_{IP}	0	+70	$^\circ\text{C}$
Operating Temperature (Industrial)		-40	+85	
Input Voltage	T_{CC}	0	5	V

Recommend Operation Environment

Parameter	Symbol	Min	Typ	Max	Unit
Supply Voltage	V_{CC}	+3.15	3.3	+3.45	V
Operating Temperature (Standard)	T_{OP}	0	-	+70	$^\circ\text{C}$
Operating Temperature (Industrial)		-40	-	+85	

Licensing

The following U.S. patents are licensed by Finisar to FluxLight, Inc.:

U.S. Patent Nos: 7,184,668, 7,079,775, 6,957,021, 7,058,310, 6,952,531, 7,162,160, 7,050,720