

Lightweight construction. Heavy-duty performance.

It's the best of both worlds. RAMPTECH® RAMPLITE PCA Layflat Ducting from Sage Parts revolutionizes PCA ducting design by combining super lightweight convenience with unsurpassed performance to tackle any and all rigors the aviation industry can throw at it.

Reinforced seams are lockstitched with high-strength polyester thread. The result? No unraveling. And three-ply fabric prevents wicking and will not degrade when exposed to Skydrol or other ramp chemicals, providing outstanding durability. It all adds up to longer service life, extensive cost savings and strong return on investment over the product lifecycle.



Outer Shell

The high-strength yellow 1680D Urethane Topcoat Cover outer shell is urethane coated for much better abrasion resistance than any lightweight PCA ducting available today. The fabric is resistant to the usual degrading effects of Glycol Alcohol or Skydrol exposure. Additionally, the outer shell is UV stabilized for protection against harmful sun degradation.

Insulation Layer

The middle layer is a 2.5mmCCF (Closed Cell Foam) fabric that is metalized on one side for superb radiant heat insulation. Its unique construction allows the material to flex without cracking or flaking. The material is also designed to inhibit growth of fungi and bacteria.

Inner Liner

The high-strength inner liner consists of a tightly woven, rip-resistant, urethane-coated nylon material (400D Urethane Topcoat Cover), which is designed to withstand the heavy wear associated with the airline industry.

Specifications

MATERIAL WEIGHT	Outer Shell: 10.0 oz/yd(sq) (339 g/m(sq)) Inner: 6.0 oz/yd(sq) (203 g/m(sq))
TEMPERATURE	-40 deg to +180deg F (-18 to -82 C)
TRAPEZOID TEAR	Outer Shell: Warp=110 lb/in ² (77,338 kg/m ²) Fill=70 lb/in ² (49,215 kg/m ²) Inner Liner: Warp=85 lb/in ² (59,761 kg/m ²) Fill 30 lb/in ² (21,092 kg/m ²)
ABRADE TO FAILURE	Outer Shell: 5,000 Cycles
DIAMETER	8 in, 12 in, and 14 in +/- 1/4 in (203.2mm, 304.8 mm, 355.6 mm)
LENGTH	10 ft, 15 ft, 20 ft, 25ft, 30 ft (3.04 m, 4.57 m, 6.09 m, 7.62 m, 9.14 m)
COLOR	Yellow (other colors available upon request)
OPTIONAL ENDS	Fold Over Hook & Loop Cuff, Soft Cuff, or Zipper Cuff

Accessories Available

Reducers

Diameters of
12 to 8 inches
14 to 8 inches

Starter Sections

Diameters of
8, 12, and 14 inches
Lengths at
3, 5, and 8 feet
Custom available upon request

Elbows

Diameters of
8, 12, and 14 inches
Angles of 45 and 90 degrees

Transition Sections

Diameters of 12 and 14 inches
Cuff combinations are Zipper
to Velcro, Velcro to Zipper, Soft
Cuff to Velcro, and Soft Cuff to
Zipper

Reducing Elbows

14 to 8 inches at 90 degrees
14 to 8 inches at 45 degrees

Wye

8x8x8 inches
12x12x12 inches
of any cuff combination

Clamps

8 inch - Part Number 501197
12 inch - Part Number 501198
14 inch - Part Number 501199



SCAN HERE to download this
Product Sheet or visit
SageParts.com

US & CANADA +1-631-501-1300
customerservice-hq@sageparts.com
MEXICO, CARIBBEAN & LATIN AMERICA
+52-311-297-8100
customerservice-mcla@sageparts.com
ASIA PACIFIC +852-2949 6257
customerservice-hk@sageparts.com

UNITED KINGDOM
+44 0 161 8642246
customerserviceuk@sageparts.com
EUROPE +331 64 02 53 00
customerservice-eu@sageparts.com



We make it easy to order online at
eSage.SageParts.com