



AQUA POINTE™

SPORTS BOTTLE FILLER

MWSBF, MW8SBF, MW12SBF

Suggested Specification

Model MW8SBF shall deliver 8.0 gph of 50°F water at 90°F ambient and 80°F inlet water. Model MW12SBF shall deliver 12.0 gph of 50°F water at 90°F ambient and 80°F inlet water. Model MWSBF is a non-refrigerated Bottle Filler and delivers ambient water. Unit shall include filtration for odor taste and chlorine reduction. Key molded components of the bottle filler contain Freshield, WHICH UTILIZES a silver-based antimicrobial compound that reduces the growth of micro-organisms and mildew to protect the surfaces from discoloration, odors and degradation. Basin shall be designed to eliminate splashing and standing water. Cooling system shall use R-134a refrigerant. Shall comply with ANSI A117.1 and ADA.

Model

MW8SBF delivers 8.0 gallons of chilled drinking water per hour.

MW12SBF delivers 12.0 gallons of chilled drinking water per hour.

MWSBF is a non-refrigerated bottle filler.

Standard Features

- > Built-in 100 micron strainer stops particles before they enter the waterway
- > Waterways are Lead-free in Materials & Construction
- > Heavy Duty steel frame
- > High Efficiency cooling tank and coil
- > Refrigerant R-134a
- > Filtration system for taste, odor and chlorine reduction

Finishes

- > Standard cabinet finish: Brushed Stainless Steel
- > Optional cabinet finish: Regency Bronze

Installation

- > Prior to roughing, consult with local, state and federal codes for proper mounting height
- > Shipped with complete instructions and wall mounting bracket
- > Removable front panels allow for easy access to filtration and refrigeration unit



Options (at additional cost)

- Ultra Violet filtration

ADA Compliant for reach ranges. These models meet guidelines for children's (ages 5 and up) accessibility providing the floor to button height is less than 40 inches and proper clear floor space is provided for frontal approach. (9-12 = 44" / Adult = 48")

Components in this fountain are lead free as defined by the Safe Drinking Water Act Amendments of 1986, and the Lead Contamination Control Act of 1988.

Product Certified to NSF/ANSI Standard 61 and is in compliance with California's Health & Safety Code Section 116875 (commonly known as AB1953). The Green Filter has been tested to the ANSI/ NSF standard 42 not by NSF

Models covered by this specification comply with all known Plumbing Codes. Listed by Underwriters' Laboratories to U.S. and Canadian standards.



Oasis International Product
Certified by NSF to
NSF/ANSI Standard 61, G

Model	50° F Drinking Water 90° F Ambient Air Temp*		115 Volts, 60 HZ			Cabinet Color Finish	Net Wt. Approx.
	Rated Capacity GPH	Base Rate GPH	Compr. HP	Full Load Amps	Rated Watts		
MWSBF						Yes	26 Lbs.
MW8SBF	8.0	8.0	1/5	4.6	340	Yes	78 Lbs.
MW12SBF	12.0	12.0	1/5	8.7	620	Yes	78 Lbs.

*Industry Standard Rating Condition 80° F inlet water temperature.

Specifications subject to change without notice

OASIS™ SPORTS BOTTLE FILLER MODEL MW8SBF, MW8SBF, MW125BF

