

## 8000T Tyre-Tack Extra

<b>Media Type</b>	Label	✓	<b>Film Type</b>	Polyethylene	
	Receipt			Polyolefin	
	Tag			Polypropylene	✓
	Wristband			Polyester	
				Polyimide	
<b>Material Type</b>	Paper		<b>Properties</b>	Cold Temperature	✓
	Synthetic	✓		Deep Freeze	
<b>Printing Technology</b>	Direct Thermal (no Ribbon Required)			High Temperature	
	Thermal Transfer (Ribbon Required)	✓		Ultra High Temperature	
<b>Adhesive Type</b>	Permanent	✓		High Tack	✓
	Removable			Chemical Resistance	<b>Mild</b>
	No Adhesive				
<b>Finish</b>	Matte		<b>Environment</b>	Indoor	✓
	Gloss	✓		Outdoor	✓

Note: 8000T Tyre-Tack Extra is not recommended for use in fanfold or print and apply applications, or for use on mobile or desktop printers due to the gloss facestock and the special adhesive. It is recommended that users ensure printers are properly maintained and regularly cleaned in order to achieve a consistent high quality print. Rolls should be stored before use according to the recommended storage conditions, and in all cases away from excessive heat and humidity.

### Additional Features

- A gloss white polypropylene suitable for outdoor exposure, offering good resistance to sunlight, in normal conditions
- Specially formulated aggressive adhesive designed to for ultimate adhesion to rubber tyres where other high-tack adhesives cannot adhere
- Excellent print quality and image durability is achieved using Zebra 4800 and 5095 resin ribbons
- Increased initial tack and ultimate adhesion when compared to 8000T Tyre-Tack
- For applications with temperatures between 40°C and 70°C, please consider 8000T Tyre-Tack
- BPA free
- Latex free adhesive

### Suggested Applications

- Direct labelling onto tyre surface indoors
- Direct labelling onto tyre surface outdoors (short term only)
- Labelling of other very rough and difficult surfaces

### Technical Specifications

	Description	Caliper
<b>Facestock</b>	Gloss white topcoated polypropylene	60 microns
<b>Adhesive</b>	Permanent ultra-aggressive rubber adhesive	52 microns
<b>Liner</b>	61gsm white glassine liner	54 microns
	<b>Total</b>	<b>166 microns ±10%</b>

**Recommended Zebra Printers:** Mid-range and high performance thermal printers

**Recommended Zebra Ribbons:** 4800, 5095

**Minimum Application Temperature:** 10°C  
When the label is applied, the environment and surface should be above this temperature

**Service Temperature Range:** -20°C to 40°C  
Following correct application and appropriate dwell time (usually 24hrs) the media will withstand this temperature range

**Recommended Storage Conditions:** 6 months duration when stored at 20° at 50% RH  
Storage of product before use

**Expected Life Span in Application:** Indoor use, for 1 year+  
Outdoor use, for up to 1 year  
Following correct application and appropriate dwell time (usually 24hrs) we expect, but do not warrant, a life span as indicated

### 180° Angle Peel Adhesion at Room Temperature (N/m):

Aluminum		Steel		Polycarbonate		Polyethylene	
5 min	24 hr	5 min	24 hr	5 min	24 hr	5 min	24 hr
956	996	980	994	988	1007	981	986

Note: For guidance only, not to be used for setting specifications



## **Product Performance and Suitability**

The information contained in this document is to be used for guidance only and is not intended for use in setting specifications. All purchasers of Zebra products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application.

Note: Rolls will typically be provided with a 'dry edge' on one side in order to improve the conversion process and reduce the risk of adhesive ooze during storage and printing.

For testing of this material, please order SAMPLE5158.