

## HIGHLIGHTS

### ARCHITECTURE LEADERSHIP

- **BASED ON AMD INFINITY ARCHITECTURE**, new 2nd Gen AMD EPYC™ Processors are the first server processors featuring 7nm hybrid multi-die design and PCIe® Gen4. The AMD EPYC Family continues to offer the most I/O and memory bandwidth<sup>1</sup> in its class.

### PERFORMANCE LEADERSHIP

- **WITH UP TO 64 HIGH PERFORMANCE CORES PER SOC**, 2nd Gen AMD EPYC Processors deliver world-record<sup>2</sup>, best-in-class performance up to a 2x<sup>3</sup> generational performance increase that outpaces Intel Xeon Platinum by up to 87%<sup>4</sup>.

### SECURITY LEADERSHIP

- **ADVANCED SECURITY FEATURES AND A SILICON-EMBEDDED SECURITY SUBSYSTEM**, 2nd Gen AMD EPYC Processors are 'hardened at the core,' helping customers guard their most important assets—their data. New 2nd Gen AMD EPYC processors, cryptographically isolate and secure more than 500 virtual machines per server using AMD Secure Encrypted Virtualization with no application changes required.

## AMD EPYC™ 7002 Series Processors: A New Standard for the Modern Datacenter

Architecture. Performance. Security. AMD EPYC 7002 Series Processors set a new standard for the modern datacenter. They help turbocharge your application performance, transform datacenter operations, and help secure mission-critical data.

AMD EPYC 7002 Series Processors set a new standard for the modern datacenter. Driven by the AMD Infinity Architecture, the AMD EPYC 7002 Family is the first x86-architecture server processor based on 7nm process technology, a hybrid, multi-die architecture, PCIe® Gen4 I/O, and an embedded security architecture. Together, these innovative capabilities deliver what you need. Performance leadership for your workloads. Protection at every layer to help secure your CPU, applications, and data—whether in your enterprise datacenter or the public cloud. And with the range of features you need to power your datacenter, you can adapt your IT infrastructure to match workload challenges you face today and into the future.

### AMD EPYC INFINITY ARCHITECTURE

AMD Infinity Architecture embodies AMD's leadership philosophy in its EPYC processor designs. It is the reason that AMD EPYC processors have leaped ahead of the market again and it is the reason to expect AMD processors to stay ahead in the future.

### A BETTER DESIGN WITH INDEPENDENT PATHS FOR INNOVATION

AMD EPYC 7002 Series Processors leapfrog the industry by using a 7nm process for the CPU cores and a 14nm process for I/O, memory access, and security functions. A system-on-chip (SoC) design eliminates the need for many external support chips, helping reduce capital and server design costs. An "all-in" feature set delivers a uniform set of features regardless of the number of processor cores.

### PERFORMANCE LEADERSHIP

Accelerated performance comes from a commitment to greater parallelism. With up to 64 cores per SOC and "Zen 2" features, the AMD EPYC 7002 Series surpasses 1st Gen AMD EPYC Processor with improved execution pipelines, higher clock rates, and up to 4x the shared Level 3 cache. The result is more than twice the performance<sup>3</sup> and up to 4x the theoretical peak floating point operations per second<sup>5</sup> (FLOPS) when compared to 1st Gen AMD EPYC Processors. The processors claim world-record performance across major industry benchmarks including SPEC CPU® 2017<sup>2</sup>, TPC®<sup>7</sup>, and VMware® VMmark® 3.1<sup>8</sup>.

# AMD EPYC 7002 Series Processors



## BETTER TOGETHER

Pairing these innovative processors with the world's first 7nm process GPU accelerator, the AMD Radeon Instinct™ MI50 and MI60, you can accelerate HPC, data analytics, artificial intelligence, and machine learning workloads. Because our 7nm technology reduces the size of each CPU core, you can enjoy

the same level of performance with roughly half the energy consumption<sup>6</sup>. The combination of DDR4-3200 DIMMs and more memory bandwidth increases the flow of data between memory and the processor so that your applications can access information faster and shorten time to results.

Model	Cores	Threads	Base Freq. (GHz)	Max. Boost Freq. (GHz) <sup>a</sup>	TDP (W)	L3 Cache (MB)	DDR Channels	Max DDR Freq. (1DPC) <sup>c</sup>	Per-Socket Theoretical Memory Bandwidth (GB/s)	PCIe <sup>®</sup> Gen 4 Lanes <sup>c</sup>	2P/1P
<b>7742</b>	64	128	2.25	3.40	225 <sup>c</sup>	256	8	3200	204.8	128	2P/1P
<b>7702</b>	64	128	2.00	3.35	200	256	8	3200	204.8	128	2P/1P
<b>7702P</b>											1P only
<b>7642</b>	48	96	2.30	3.30	225 <sup>c</sup>	256	8	3200	204.8	128	2P/1P
<b>7552</b>	48	96	2.20	3.30	200	192	8	3200	204.8	128	2P/1P
<b>7542</b>	32	64	2.90	3.40	225 <sup>c</sup>	128	8	3200	204.8	128	2P/1P
<b>7502</b>	32	64	2.50	3.35	180	128	8	3200	204.8	128	2P/1P
<b>7502P</b>											1P only
<b>7452</b>	32	64	2.35	3.35	155	128	8	3200	204.8	128	2P/1P
<b>7402</b>	24	48	2.80	3.35	180	128	8	3200	204.8	128	2P/1P
<b>7402P</b>											1P only
<b>7352</b>	24	48	2.30	3.20	155	128	8	3200	204.8	128	2P/1P
<b>7302</b>	16	32	3.00	3.30	155	128	8	3200	204.8	128	2P/1P
<b>7302P</b>											1P only
<b>7282</b>	16	32	2.80	3.20	120	64	8	3200	85.3 <sup>b</sup>	128	2P/1P
<b>7272</b>	12	24	2.90	3.20	120	64	8	3200	85.3 <sup>b</sup>	128	2P/1P
<b>7262</b>	8	16	3.20	3.40	155	128	8	3200	204.8	128	2P/1P
<b>7252</b>	8	16	3.10	3.20	120	64	8	3200	85.3 <sup>b</sup>	128	2P/1P
<b>7232P</b>	8	16	3.10	3.20	120	32	8	3200	85.3 <sup>b</sup>	128	1P only

a. Maximum single-core frequency at which the processor is capable of operating.

b. Performance optimized for 4 channels with DDR4-2667 DIMMS.

c. Some supported features and functionality of 2nd Gen AMD EPYC processors require a BIOS update from your server manufacturer when used with a motherboard designed for 1st Gen AMD EPYC Processors. A motherboard designed for 2nd Gen AMD EPYC Processors is required to enable all available functionality. ROM-06.

## FOOTNOTES

The following comparisons were current as of August 7, 2019

1. EPYC 7002 series has 8 memory channels, supporting 3200 MHz DIMMs yielding 204.8 GB/s of bandwidth vs. the same class of Intel Scalable Gen 2 processors with only 6 memory channels and supporting 2933 MHz DIMMs yielding 140.8 GB/s of bandwidth.  $204.8 / 140.8 = 1.454545 - 1.0 = .45$  or 45% more. AMD EPYC has 45% more bandwidth. Class based on industry-standard pin-based (LGA) X86 processors. ROM-11
2. Based on SPECrate<sup>®</sup>2017 peak integer scores. A 2P EPYC™ 7742 processor powered server has higher SPECrate<sup>®</sup>2017\_int\_peak score of 749 and a base score of 682 as of August 7, 2019, <http://spec.org/cpu2017/results/res2019q3/cpu2017-20190722-16242.html>. The next highest int\_peak score with a 2P Intel Platinum 9282 of 676 and a base score of 643, <http://spec.org/cpu2017/results/res2019q3/cpu2017-20190624-15369.pdf>, on July 28, 2019. ROM-114.
3. Results as of 8/7/2019 using SPECrate<sup>®</sup>2017\_int\_base. The AMD EPYC 7742 2P score is 654, <https://spec.org/cpu2017/results/res2019q3/cpu2017-20190722-16242.html>. AMD EPYC 7601 2P score of 304, <http://spec.org/cpu2017/results/res2019q2/cpu2017-20190411-11817.pdf>.  $654/304 = 2.15$  or 2x higher integer performance for the EPYC 7742. ROM-37
4. Results as of 8/7/2019 using SPECrate<sup>®</sup>2017\_int\_base. AMD EPYC 7742 score of 682, <https://spec.org/cpu2017/results/res2019q3/cpu2017-20190722-16242.html>. Intel Platinum 8280L score 364, <http://spec.org/cpu2017/results/res2019q2/cpu2017-20190429-12779.pdf>, July 28, 2019. ROM-38.
5. Based on standard calculation method for determining FLOPS. ROM-04
6. Based on June 8, 2018 AMD internal testing of same-architecture product ported from 14 to 7 nm technology with similar implementation flow/methodology, using performance from SGEMM. EPYC-07
7. 8-node EPYC 7702 result at <http://www.tpc.org/3341>. Previous #1 published at <http://www.tpc.org/3306>. Product availability 8/7/2019. ROM-139.
8. AMD EPYC 7702 VMware<sup>®</sup> VMmark<sup>®</sup> 3.1 score of 12.88 can be found at <https://www.vmware.com/content/dam/digitalmarketing/vmware/en/pdf/vmmark/2019-08-07-HPE-ProLiant-DL385Gen10.pdf>. Product available Aug 7, 2019. The next highest score, 9.02, with the Intel Xeon 8280, can be found at <https://www.vmware.com/products/vmmark/results3x.0.html>. VMware VMmark 3.x results can be found at <https://www.vmware.com/products/vmmark/results3x.html>. ROM-35.