

Simplifying the ADA Final Exam

- The primary difference between Title II regulations and Title III regulations of the 2010 ADA Standards, is that Title II establishes _____ for _____.**
 - Guidelines, commercial facilities
 - Laws, facilities built with public funds
 - Guidelines, facilities built with public funds
 - Laws, commercial facilities
- If the building cannot be made accessible to wheelchairs, accessibility _____.**
 - Must still be provided for persons with other types of disabilities
 - Is no longer mandatory for that structure
 - Must be provided at a later date if a building occupant becomes disabled
 - Can be provided in a separate structure
- When considering required accessibility alterations, a _____ is defined as a major activity for which the facility was created.**
 - Use classification
 - Primary function
 - Point of service
 - Work activity
- In portions of residential buildings being used for commercial purposes, portions used by _____ must still comply.**
 - Residents in mobility aids
 - The public
 - Visitors of residential tenants
 - Anyone requiring a service animal
- Unless exempted elsewhere, how many accessible parking spaces must be provided in a parking facility with 51-75 total spaces?**
 - 5
 - 1
 - 3
 - 7
- Raised shapes providing a detectable warning on a walk surface will be in a _____ shape.**
 - Recessed dimple
 - Raised bar
 - Truncated dome
 - Flattened pyramid
- A required accessible primary entrance to a residential dwelling unit, may not enter a _____.**
 - Bedroom
 - Great room
 - Shared vestibule
 - Dining room
- When an accessible route turns 180 degrees around an element with at least 60" of clear width at the turn, the approach to the turn must be at least _____ wide.**
 - 36"
 - 42"
 - 48"
 - 60"
- On accessible routes less than _____ wide, passing spaces will be provided less than _____ apart.**
 - 60", 200'
 - Two wheelchairs, 60 feet
 - 36", 60'
 - Two wheelchairs, 200 feet
- Handrails for adults must be _____ above the surface, another for children can be _____ high.**
 - 33"-36", 26"-28"
 - 34"-38", 26"-28"
 - 34"-38", 28"
 - 42", 18"
- No projections are allowed into required clear openings, lower than _____ above the floor.**
 - 34"
 - Handle height
 - 36"
 - 27"
- A distance of at least _____" should be maintained between two hinged or pivoted doors or gates in series.**
 - 60
 - 48
 - 36
 - 32

13. Space between the finish surface and 9" above that surface is considered _____.
 a. Unusable for clearance
 b. Storage space, if covered
 c. Swing space
 d. Toe clearance
14. Objects 27"-80" above finish floor, can protrude only _____" into a circulation path.
 a. 4
 b. 6-9
 c. 2
 d. 4½
15. Elevator control buttons shall be identified by tactile characters, with raised character and braille designations immediately to the _____ of the control button they designate.
 a. Left
 b. Right
 c. Top
 d. Bottom
16. _____ wheelchair spaces are required in an assembly area having 301-500 seats
 a. 2
 b. 6
 c. 8
 d. 5
17. Licensed facilities, where patient stays exceed 24 hours, must _____.
 a. Make all parking spaces accessible.
 b. Provide accessible sleeping rooms
 c. Provide overnight accommodations for companions
 d. Have centralized nursing stations
18. Where work surfaces are provided for non-employees, at least _____% will be accessible.
 a. 7½
 b. 10
 c. 5
 d. 2
19. Renovation of general holding and housing cells need not include accessible cells, unless that is required by the _____.
 a. Jail administrator
 b. Prisoner advocacy council
 c. Attorney General
 d. A professional negotiator
20. Where visible doorbell signals are in sleeping areas, they will have _____.
 a. A remote response to allow access without rising
 b. Controls to deactivate the signal
 c. A strobe that slowly increases in intensity
 d. An easily removeable cover
21. Accessible dressing rooms should have bench seats installed _____ high.
 a. 17"-19"
 b. Knee
 c. 14"-16"
 d. 2" below wheelchair seat
22. The sound level of audible notification appliances will be no more than _____.
 a. 10dB above ambient noise
 b. 110dB
 c. 3500Hz
 d. 95dB
23. The firmer the carpeting and backing, the _____.
 a. Lower the roll resistance
 b. Less future maintenance required.
 c. Less likely it is to be perceived as real carpet
 d. More expensive to purchase
24. To remain accessible, vertical changes in levels not including a bevel, can be no higher than _____".
 a. 3/16"
 b. 1/8"
 c. ½"
 d. ¼"
25. Where a sand box is provided, an accessible route must connect to _____.
 a. The principle play area entry
 b. The bottom of the sandbox
 c. The base of the nearest slide
 d. The sand box border
26. If 14-16 elevated play components are provided, there must also be a minimum of _____ ground level components on an accessible route.
 a. 3
 b. 5
 c. 7
 d. 8