

Final Exam

Continuing Education Course #140 Campgrounds The Basics of Design

 1. What provides a campground the means to increasing its revenue without a large monetary investment a. Paved roads b. Sanitary sewer systems c. Hiking trails d. Primitive campsites
 2. A Self-Contained Unit has what features? a. A flushable toilet b. Internal potable water storage tanks c. Internal sewage storage tanks d. All of the above
 3. True or False: You should never rely on regulatory reviewers to catch the design flaws in your plans. a. True b. False
4. The bathhouse service area is defined by the a. The design engineer b. The local regulatory agency c. The Department of Interior d. None of the above
 5. True or False: Sanitary dump stations are typically required for all campgrounds that serve RVs. a. True b. False
6. A sanitary dump station will generally include ? a. A sloped apron b. A water supply c. A sign stating "Water not safe for drinking" d. All of the above
7. Which primitive campsites will have a greater negative impact to the environment? a. Designated b. Non-designated c. Neither
8. What is the typical size of a tent camping site?

 a. 12-ft by 30-ft in size with a 12-ft by 12-ft camp pad b. 12-ft by 30-ft in size with a 20-ft by 20-ft camp pad c. 20-ft by 30-ft in size with a 20-ft by 20-ft camp pad d. 24-ft by 40-ft in size with a 24-ft by 20-ft camp pad
9. What electrical service is typically supplied to a tent camping site? a. 110-volt 20-amp b. 110-volt 30-amp c. 110-volt 50-amp d. None of the above
10. Where are the water, sewer, and electrical connections found on a RV? a. Near the front of the vehicle on the driver's side b. Near the rear of the vehicle on the driver's side c. Near the front of the vehicle on the passenger's side d. Near the rear of the vehicle on the passenger's side
11. What is the preferred RV campsite size? a. approximately 12-ft by 30-ft in size with an adjacent 20-ft by 20-ft camp pad b. approximately 20-ft by 30-ft in size with an adjacent 20-ft by 20-ft camp pad c. approximately 12-ft by 50-ft in size with an adjacent 20-ft by 20-ft camp pad d. approximately 20-ft by 50-ft in size with an adjacent 20-ft by 20-ft camp pad
12. What is the maximum elevation difference of the four corners of a RV parking pad? a. 4 inches of elevation difference or 6-8 inches in extreme cases b. 6 inches of elevation difference or 8-10 inches in extreme cases c. 8 inches of elevation difference or 10-12 inches in extreme cases d. 10 inches of elevation difference or 12-14 inches in extreme cases
13. Most RV jack levelers will not lift a tire completely off the ground?○ a. True○ b. False
14. What size electrical service is typically supplied at a RV site? a. 20-amp b. 30-amp c. 50-amp d. All of the above.
 15. What is the preferred design choice for campground drives? a. One-way roads b. Two-way roads c. One-way roads with pedestrian lanes d. None of the above.
16. What is the posted speed limit in most campgrounds? a. 5 or 10 mph b. 10 or 15 mph c. 15 or 20 mph d. 20 or 25 mph

 17. Which of the following is true for curved campsites? a. They should only be used on one-way drives b. They should only be used on the left side of the road c. They should never curve to the right d. All of the above
18. Which of the following is NOT true for one-way drives in campgrounds? ○ a. They provide quick easy access to campsites ○ b. They require more maneuvering room to get into the campsite ○ c. They minimize congestion on the drives by drivers not blocking two lanes of traffic when backing into campsites ○ d. They increase safety for drivers and pedestrians by limiting traffic flow to a single direction
19. The radius on a curved campsite should not be less than a? a. 25-foot radius b. 50-foot radius c. 80-foot radius d. 100-foot radius
20. The most common pull-thru campsite is the loop pull-thru. a. Inside b. Outside
21. What is the recommended RV pad width? a. 12 feet b. 14 feet c. 20 feet d. 24 feet
22. Which traffic calming design method should be avoided in campgrounds? a. Curves in the road b. Stop signs c. Speed bumps d. Posted speed limits
23. Boardwalk guard railings should have slat spacing no greater than inches in width? a. 2 b. 4 c. 6 d. 8
24. True or False: ADA campsites should be located as close as possible to an ADA bathhouse. a. True b. False
25. True or False: Campgrounds are never required to provide street names if the campsite numbers are posted. a. True b. False