



Note: The product images shown may change over time as products are updated.

## Dimensions

50

## Part Number


**CQP2-5030N-SRU4T**

## Features

- Capacitive sensors for the reliable detection of liquids, plastics, powders, pellets and pastes
- Available in plastic or stainless steel housings
- Connectable with a pre-wired cable of any length or with a quick-connector
- Available with PNP, NPN, AC or AC/DC output functions
- Mountable with a shielded or unshielded construction with adjustable sensitivity

## Connection

- 1 - Brown
- 2 - White
- 3 - Blue
- 4 - Black



## Technical Data

|                            |   |
|----------------------------|---|
| Sensing Type               | Capacitive Sensor                                   |
| Body Style                 | Square  |
| Sensor Housing Material    | PBT   |
| Sensor Face Material       | PBT   |
| Mounting Style             | Non-Shielded  |
| Diameter                   | Square  |
| Sensing Range:             | 2-30 mm   |
| Output Type:               | NPN   |
| Output Function            | Normally Open and Normally Closed                   |
| Connection                 | Connect   |
| Body Length                | 50  |
| Operating Voltage          | 10-30 VDC   |
| Switching Frequency        | 100 Hz  |
| Operating Temperature      | -25 °C - +70 °C                                     |
| Overload Trip Point        | 350 mA  |
| Hysteresis:                | <15% (Sr)   |
| IP Rating:                 | IP67  |
| Shock Rating:              | IEC 60947-5-2, Part 7.4.1/IEC 60947-5-2, Part 7.4.2 |
| Short Circuit Protected    | YES   |
| Reverse Polarity Protected | YES   |
| Connector Type             | 4-Pin EURO Quick-Connect                            |
| Current Consumption        | <10 mA  |



In the USA: 1889 Maryland Ave., Niagara Falls, NY 14305  
 In Canada: 3419 Mainway, Burlington, ON L7M 1A9  
 Toll Free: 1-800-644-1756 • Fax: 888-283-2127  
 service@htmsensors.com