



Note: The product images shown may change over time as products are updated.

Part Number

FCP2-3015NU


Features

Inductive Proximity Sensors are used in a wide variety of manufacturing operations where a metal target needs to be sensed. HTM Sensors inductive proximity sensors have a Lifetime Warranty, a CSA or UL approval, and a huge inventory for same-day shipping. For tougher applications where the sensors need more range to stay out of harm's way, or to withstand high temperatures, weld spatter, chemical exposure, oil or other rough environments, HTM Sensors has the widest range of proximity sensors on the market.

Connection



Dimensions



Technical Data

| | |
|----------------------------|--|
| Body Style | Cylindrical |
| Sensor Housing Material | PBT Plastic |
| Sensor Face Material | PBT Plastic |
| Mounting Style | Unshielded |
| Diameter | 30 mm Threaded |
| Sensing Range: | 15 mm range |
| Output Type: | Namur Output |
| Output Function | Namur Output |
| Connection | Pre-Two Wired Cable Connect |
| Connector Type | Cable |
| Operating Voltage | 6-12VDC |
| Switching Frequency | 100 Hz |
| Operating Temperature | -25 °C – +70 °C |
| Current Consumption | >2.2mA(OFF) |
| IP Rating: | IP68 |
| EMC Rating | RFI>3V/m / EFT>1kV / ESD>4Kv (contact) |
| Shock Rating: | IEC 60497-5-2 Part 7.4.1&7.4.2 |
| Short Circuit Protected | NO |
| Reverse Polarity Protected | NO |
| Max Current | — |
| Leakage Current | — |
| Surge Current | - |
| Response Time | 1 ms/1 ms |
| Hysteresis | <15%(Sr) |
| Overload Trip Point | - |
| Weld Field Immune | No |
| Weld Spatter Resistant | No |
| Body Length (mm) | 40 |