



## B2D12 Copper Braid, 12" Long, 2 Braids, 2 Holes 2 Ferrules, 7/16" Stud, 1-1/4" Stud Hole Spacing, 380 amps Indoor, 455 amps Outdoor

By Burndy  
Catalog # B2D12



Copper Braid, 12" Long, 2 Braids, 2 Holes 2 Ferrules, 7/16" Stud, 1-1/4" Stud Hole Spacing, 380 amps Indoor, 455 amps Outdoor.

### Features

- Most Burndy braid are UL Listed and CSA Certified
- Pressed seamless copper ferrules provide added durability and prevent fraying, providing extra strength for a robust bonding connection
- Braid is especially suited for applications that require flexibility or resistance to vibration
- Extra fine stranding gives enhanced flexibility
- Ferrules clearly marked with Burndy braid type and UL markings (where appropriate)
- Available in custom lengths and hole sizes to suit your needs (contact your local sales representative for non-standard configurations)
- For assistance in finding the perfect braid for your needs click here for our Braid Configurator Tool:  
[www.hubbell.com/config/BRAID](http://www.hubbell.com/config/BRAID)

### Application

Flexible copper braid jumpers designed to take up linear expansion and contraction, compensate for misalignment and absorb vibratory movement of electrical equipment and devices

### General

|                                       |               |
|---------------------------------------|---------------|
| Catalog Number                        | B2D12         |
| Connector Type                        | Braid         |
| EU RoHS Indicator                     | Yes           |
| Material                              | Copper        |
| Material - Ferrules                   | Y             |
| Physical Attribute - Number of Braids | 2             |
| Plated                                | Y             |
| Sub Brand                             | BRAID         |
| Type                                  | B, Flexible   |
| UPC                                   | 781810807002  |
| UPC 12 Digit                          | 7818108070022 |

### Dimensions

|                                 |            |
|---------------------------------|------------|
| Dimension - D inch              | 2.5        |
| Dimension - Hole Size inch      | 0.44       |
| Dimension - L Length Overall mm | 305 mm     |
| Dimension - Length Overall inch | 12.00 inch |
| Dimension - N inch              | 0.62       |
| Dimension - Pad Width inch      | 0.94       |
| Length                          | 12 in      |

### Electrical Ratings

|                           |     |
|---------------------------|-----|
| Rating - Indoor Amperage  | 380 |
| Rating - Outdoor Amperage | 455 |

### Certifications And Compliance

|                                    |       |
|------------------------------------|-------|
| Certification - CSA Approved       | Yes   |
| Certification - ETL                | No    |
| Certification - UL Recognized      | No    |
| Certification - cULus              | No    |
| Industry Standard(s)               | UL467 |
| Standards - Industry Standards Met | UL467 |
| Standards - RoHS Compliance Status | CM    |
| UL Listed                          | Yes   |

### Product Assets

- [3D Models - B2D12\\_MODEL-IGES](#)
- [3D Models - B2D12\\_MODEL-STEP](#)
- [3D Models - B2D12\\_MODEL-PDF](#)
- [Catalogs - BURNDY Master Catalog - Section E2 - Mechanical Grounding](#)
- [Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog](#)
- [Customer Notices - Prop 65 Notice](#)
- [Interactive Catalog - BURNDY Full-Line Digital Catalog](#)
- [Product Cross Section Image\(s\) - BUR\\_BD\\_Lineart](#)
- [Sales Drawings - SE210201-02\\_DI](#)
- [Specifications - B2D12](#)



A Hubbell brand

©2024 Hubbell Incorporated. All rights reserved  
BRDY\_MX-B2D12-SPEC-EN | REV 10/2024