




Color :  Orange

UPC Code : 078477900116

Country Of Origin : Mexico

Available Colors :



D8200-IG

15 Amp Decora Plus Isolated Ground Duplex Receptacle/Outlet, Hospital Grade, Self-Grounding

Decora Plus Isolated Ground Duplex Receptacle Outlet, Heavy-Duty Hospital Grade, Smooth Face, 15 Amp, 125 Volt, Back or Side Wire, NEMA 5-15R, 2-Pole, 3-Wire, Self-Grounding - Orange

ROHS Compliant : Yes

Technical Information

AC Horsepower Rating

Flammability : Rated V-0 per UL 94

Horsepower Rating : 1/2 HP

Operating Temperature : -40° C to 75°C

Electrical Specifications

Amperage : 15 A

Body Material : PBT Polyester Blend

Dielectric Voltage : Withstands 3000 V minimum

Face Material : PBT Polyester Blend

Ground Clips : Brass

Ground Contacts : 0.030" Brass

Grounding : Self-Grounding

Grounding Screw : #8 hex head, triple drive Brass

Line Contacts : 0.030" Phosphor Bronze

Mounting Screws : Triple-Drive Plated Steel

Pole : 2

Strap Material : Steel

Temperature Rise : Max 30 °C after 250 cycles OL at 200 percent rated current

Terminal Clamps : Brass

Terminal Screws : #8 Triple-Drive Brass

Voltage : 125 VAC

Wire : 3

Environmental Specifications

Flammability : Rated V-0 per UL 94

Operating Temperature : -40° C to 75°C

Material Specifications

Body Material : PBT Polyester Blend

Brand : Decora Plus

Color : Orange

Product ID : Ratings are permanently marked on device

Terminal Accom. : #14 AWG - #10 AWG

Terminal ID : Brass - Hot, Green - Ground, Silver - Neutral

Termination : Back or Side Wire

Wire Type : Stranded or Solid

Color / Feature : Orange

Device Type : Duplex Receptacle Outlet

Face Material : PBT Polyester Blend

Feature 4 : Smooth Face

Function : Isolated Ground

Grade : Heavy-Duty Hospital Grade

Ground Clips : Brass

Ground Contacts : 0.030" Brass

Grounding Screw : #8 hex head, triple drive Brass

Line Contacts : 0.030" Phosphor Bronze

Mounting Screws : Triple-Drive Plated Steel

Strap Material : Steel

Terminal Clamps : Brass

Terminal Screws : #8 Triple-Drive Brass

Mechanical Specifications

Horsepower Rating : 1/2 HP

Product ID : Ratings are permanently marked on device

Screw Terminal Torque : 14-18 in-lbs

Shutter Mechanism : Acetal

Terminal Accom. : #14 AWG - #10 AWG

Terminal ID : Brass - Hot, Green - Ground, Silver - Neutral

Termination : Back or Side Wire

Wire Type : Stranded or Solid

Product Features

ANSI : C-73

Applicable Standards : UL 498, Fed Spec W-C-596, CSA C22.2. No. 42

Brand : Decora Plus

Certification/Listing : cULus, NOM-ANCE

Color : Orange

Color / Feature : Orange

Device Type : Duplex Receptacle Outlet

Feature 4 : Smooth Face

Function : Isolated Ground

Grade : Heavy-Duty Hospital Grade

RoHS : RoHS Compliant

Standards & Certifications

ANSI : C-73

Applicable Standards : UL 498, Fed Spec W-C-596, CSA C22.2. No. 42

Certification/Listing : cULus, NOM-ANCE

RoHS : RoHS Compliant

Warranty

Amperage : 15 A

Dielectric Voltage : Withstands 3000 V minimum

Grounding : Self-Grounding

Pole : 2

Temperature Rise : Max 30 °C
after 250 cycles OL at 200
percent rated current

Voltage : 125 VAC

Warranty : 10-Year Limited

Wire : 3

Patents *

MX321216	US8777674
US8684771	MX324598

This list is provided for patent marking purposes only. A good faith effort is made to maintain the accuracy and completeness of this list. No legal inference should be drawn from the omission of a patent from this list.

SPECIFICATION SUBMITTAL

JOB NAME: 	CATALOG NUMBERS:
JOB NUMBER: 	

Leviton Manufacturing Co., Inc
201 North Service Road, Melville, NY 11747
Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.
T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.
165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 ·
FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.
Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)
5386- 1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com
© 2024 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without
notice.

Leviton has a global presence.
If you would like to know where your local Leviton office is located please go to:
www.leviton.com/international/contacts

© 2024 Leviton Manufacturing Co., Inc.