



Color :

Black-White

UPC Code: 078477807873

Country Of Origin: Mexico

NEMA:

L5-30R

Available Colors:





Yellow-White

2613

Locking Connector, 30 Amp, 125 Volt, Industrial Grade - Black & White

30 Amp, 125 Volt, NEMA L5-30R, 2P, 3W, Locking Connector, Industrial Grade, Grounding - Black/White

ROHS Compliant: Yes

Leviton's Black & White line of industrial grade plugs, connectors, flanged inlets, and outlets offer superior performance, long lasting reliability and features that are backed by a limited lifetime warranty:

- One piece contacts reduce friction and overheating
- Unique cord clamp accepts wide range of cord sizes
- Rugged nylon construction resists impact, sunlight, chemicals, and rough use
- Industry exclusive limited lifetime warranty

Technical Information

Electrical Specifications Environmental Specifications

Amperage: 30 A **Environment:** Dry

Current Interrupting: Certified Flammability: Rated HB or for current interrupting at full better UL94

Operating Temperature: -40°

C to 60°C

rated current

Dielectric Voltage: Withstands 2000V per UL498

Grounding: Grounding

Pole: 2

Temperature Rise: Max 30C after 250 cycles OL at 200 percent rated current

Voltage: 125 VAC

Wire: 3

Material Specifications

Assembly Screws: Steel, Zinc

Plated

Back Cover: Thermoplastic

Blades/Contacts: Solid Brass

Body Material: Impact

Modified Nylon

Clamp Insert: Nylon

Color: Black-White

Cord-Clamp: Nylon

Terminal Screws: Brass

Mechanical Specifications

At Rated Voltage: 2 HP

Cord Range: 0.520 to 0.930

Product ID: Ratings are permanently marked on device

Terminal Accom.: 18-10 AWG

Terminal ID: Brass-Hot. Green-Ground, Silver-Neutral

Torque Range: 10-14 in-lbs

Wire Gauge: 16-8 AWG

Wire Module: Nylon

Product Features Standards and Certifications

Brand: Black and White **ANSI**: C-73

Color: Black-White CSA C22.2 No. 42: File LR-406

Device Type : Locking **NEMA :** WD-6

Connector

NEMA: L5-30R UL Fed Spec WC-596: File

E13393

NOM: 057

UL498: File E13393

Warranty: Limited Lifetime

Warranty

Patents*

US10658142 US10658142 US10658142 US10971319 US10971319 US10971319

This list is provided for patent marking purposes only. A good faith effort is made to maintain the accuracy and completeness of this list. No legal inference should be drawn from the omission of a patent from this list.

Dimensional Drawing

Cover Screw Dimensions DOUBLE THREAD (THREAD FORMING): #10-32 - 2A PITCH: #10 THREAD, 32 THREADS PER INCH 77 - 72* THREAD DEPTH

SPECIFICATION SUBMITTAL

JOB NAME:	CATALOG NUMBERS:
JOB NUMBER:	

Leviton Manufacturing Co., Inc

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.

T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 · FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52) 5386- 1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2024 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to: www.leviton.com/international/contacts

© 2024 Leviton Manufacturing Co., Inc.