

3430



30 Amp, 120/208 Volt, Flush Mount Locking Receptacle,
Industrial Grade

30 Amp, 120/208 Volt 3-Phase Y, NEMA Non-NEMA, 4P, 4W,
Flush Mtg Locking Receptacle, Industrial Grade, Non-Grounding -
BLACK

Leviton's line of Extra Heavy-Duty Industrial Grade locking receptacles are designed and manufactured to withstand the harsh conditions typically associated with industrial environments. Available in a wide variety of configurations, including isolated ground, tamper-resistant, hospital grade, etc., these Industrial Grade devices are the electrical contractor's choice for use in factories, schools, hospitals and commercial office buildings.

UPC Code : 078477821596

Country Of Origin : Mexico

Technical Information

Electrical Specifications

Amperage : 30 A

Current Limiting : Full Rated
Current

Dielectric Voltage :
Withstands 2000V per UL498

Grounding : Non-Grounding

Phase : 3-Phase WYE

Pole : 4

Temperature Rise : Max 30C
after 250 cycles OL at 200
percent rated current

Voltage : 120/208 VAC

Wire : 4

Environmental Specifications

Environment : Dry

Flammability : Rated V-2 per
UL 94

Operating Temperature : -40°
C to 60°C

Material Specifications

Base Material : Nylon

Color : Black

Face Material : Nylon

Grounding Screw : Brass 8-32

Line Contacts : Brass .040
Thick

Strap Material : Nickel-Plated
Brass

Terminal Screws : Brass 10-32

Yoke : Nickel-Plated Brass .
050 Thick

Mechanical Specifications

Product ID : Ratings and
NEMA I.D. permanently marked
on device

Screw Terminal Torque : 14-
18 in-lbs

Terminal Accom. : 18-10 AWG

Terminal ID : Brass-Hot,
Green-Ground, Silver-Neutral

Termination : Back & Side

Product Features

Color : Black

Standards and Certifications

ANSI : C-73

Device Type : Locking
Receptacle

Voltage : 120/208 VAC

CSA C22.2 No. 42 : File LR-406

NEMA : WD-6

NOM : 057

UL498 : File E13399

Warranty : Limited Lifetime
Warranty Warranty

SPECIFICATION SUBMITTAL

JOB NAME: <input type="text"/>	CATALOG NUMBERS: <input type="text"/>	<input type="text"/>
JOB NUMBER: <input type="text"/>	<input type="text"/>	<input type="text"/>

Leviton Manufacturing Co., Inc

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.
T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 ·
FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)
5386- 1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2024 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without
notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:
www.leviton.com/international/contacts

© 2024 Leviton Manufacturing Co., Inc.