



4710

15 Amp, 125 Volt, Single Locking Receptacle, Industrial Grade

15 Amp, 125 Volt, NEMA L5-15R, 2P, 3W, Single Locking Receptacle, Industrial Grade, Grounding - BLACK

Leviton's Industrial Grade Locking Devices are built to provide unparalleled quality and superior performance in the most severe industrial settings. Leviton combines the best materials available with superior production standards to produce a broad selection of Locking Devices of unmatched flexibility and dependability.

- Ideal for motor loads, such as shop vacs and pool pumps, and generators

UPC Code : 078477796986

Country Of Origin : Mexico

NEMA :  L5-15R

Technical Information

AC Horsepower Ratings

At Rated Voltage : 1/2 HP

Electrical Specifications

Amperage : 15 A

Current Limiting : Full Rated Current

Dielectric Voltage :
Withstands 2000V per UL498

Grounding : Grounding

Pole : 2

Temperature Rise : Max 30C
after 250 cycles OL at 200
percent rated current

Voltage : 125 VAC

Wire : 3

Environmental Specifications

Environment : Dry

Flammability : Rated V-2 per
UL 94

Operating Temperature : -40°
C to 60°C

Material Specifications

Body Material : Nylon

Color : Black

Face Material : Nylon

Grounding Screw : Brass 8-32

Line Contacts : Brass .031
Thick

Strap Material : Nickel-Plated
Brass

Terminal Screws : Brass 10-32

Yoke : Zinc-Plated Steel

Mechanical Specifications

Cord Range : 0.230 to 0.700

Product Features

Color : Black

Device Type : Locking
Receptacle

Product ID : Ratings and
NEMA I.D. permanently marked
on device

NEMA : L5-15R

Screw Terminal Torque : 14-
18 in-lbs

Terminal Accom. : 18-10 AWG

Terminal ID : Brass-Hot,
Green-Ground, Silver-Neutral

Termination : Side

Standards and Certifications

ANSI : C-73

CSA C22.2 No. 42 : File LR-406

NEMA : WD-6


NOM : 057

UL Fed Spec WC-596 : File
E13399

UL498 : File E13399

Warranty : Limited Lifetime
Warranty Warranty

Wiring Diagram



SPECIFICATION SUBMITTAL

JOB NAME: 	CATALOG NUMBERS: 	
JOB NUMBER: 		

Leviton Manufacturing Co., Inc

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.

T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 ·

FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52) 5386- 1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2024 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:
www.leviton.com/international/contacts

© 2024 Leviton Manufacturing Co., Inc.