



**Color :**  Ivory

**UPC Code :** 078477151211

**Country Of Origin :** United States

**Available Colors :**



# 1451-ICP

15 Amp Single-Pole Toggle Switch, Non-Grounding, Ivory

15 Amp, 120 Volt, Toggle Framed Single-Pole AC Quiet Switch, Residential Grade, Non-Grounding, Quickwire Push-In & Side Wired, - Ivory

Tried-and-true toggle designs, Leviton Residential Grade AC Quiet Switches cover all the bases; they install easily and are available in standard and illuminated versions. Their toggles and frames are constructed of impact-resistant thermoplastic, and they feature large head, hardened triple-drive screws for easy installation. Leviton's traditional switches are compatible with a wide range of Leviton plastic and metal wallplates.

## Technical Information

### Product Features

**Actuator Material :**

Thermoplastic

**Amperage :** 15 A

**Body Material :** Thermoplastic

**Color :** Ivory

**Feature :** Framed

**Grounding :** Non-Grounding

**HP Rating :** 1/2HP-120V

**Max. Amperage :** 12 Amp

**Pole :** 1

### **Standards and Certifications**

: UL/CSA

**Strap Material :** Steel

**Terminal Accom. :** Side wiring

accepts #10, #12 and #14

AWG copper (CU) or #10 and

#12 copper clad (CC) wire,

Quickwire push-in terminals

accept #14 AWG solid copper

(CU) wire only

**Termination :** Quickwire Push-

In & Side

**Torque Range :** 14 – 18 in.-lbs

**Type :** Toggle Switch


**Voltage :** 120 VAC

**Warranty :** 2-Year Limited

## Features and Benefits

- Side wiring accepts #10, #12 and #14 AWG copper (CU) or #10 and #12 copper clad (CC) wire
- Quickwire push-in terminals accept #14 AWG solid copper (CU) wire only
- NOTE: In Canada, a general-use switch does not require attachment to a grounding/bonding wire when installed in a grounded/bonded flush device box.

## Wiring Diagram



### SPECIFICATION SUBMITTAL

JOB NAME: <input style="width: 90%;" type="text"/>	CATALOG NUMBERS: <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 50%; height: 20px;"></td> <td style="width: 50%; height: 20px;"></td> </tr> <tr> <td style="height: 20px;"></td> <td style="height: 20px;"></td> </tr> </table>				
JOB NUMBER: <input style="width: 90%;" type="text"/>					

#### Leviton Manufacturing Co., Inc

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.

T. Monday-Friday): +1-800-824-3005

#### Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 ·

FAX: +1-800-824-3005 · [www.leviton.com/canada](http://www.leviton.com/canada)

#### Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)

5386- 1797 · [www.leviton.com.mx](http://www.leviton.com.mx)

#### Visit our Website at: [www.leviton.com](http://www.leviton.com)

© 2024 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

#### Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:

[www.leviton.com/international/contacts](http://www.leviton.com/international/contacts)

© 2024 Leviton Manufacturing Co., Inc.