



# 5362-SW

20 Amp Duplex Receptacle/Outlet, Industrial Grade, Self-Grounding

Duplex Receptacle Outlet, Heavy-Duty Industrial Specification Grade, Smooth Face, 20 Amp, 125 Volt, Back and Side Wire, NEMA 5-20R, 2-Pole, 3-Wire, Self-Grounding - White

**ROHS Compliant :** Yes

Leviton's line of Extra Heavy-Duty Industrial Grade receptacles are designed and manufactured to withstand the harsh conditions typically associated with industrial environments. Available in a wide variety of configurations, including isolated ground, tamper-resistant, hospital grade, etc., these Industrial Grade devices are the electrical contractor's choice for use in factories, schools, hospitals and commercial office buildings.

**Color :**  White

**UPC Code :** 078477141151

**Country Of Origin :** Mexico

**NEMA :**  5-20R

## Available Colors :



## Technical Information

### AC Horsepower Ratings

**At Rated Voltage :** 1 HP

### Electrical Specifications

**Amperage :** 20 A

**Current Limiting :** Full Rated Current

**Dielectric Voltage :**  
Withstands 2000V per UL498

**Grounding :** Self Grounding

**Pole :** 2

**Temperature Rise :** Max 30C after 250 cycles OL at 200 percent rated current

**Voltage :** 125 VAC

**Wire :** 3

### Environmental Specifications

**Flammability :** Rated V-2 per UL 94

**Operating Temperature :** -40° C to 60°C

### Material Specifications

**Body Material :** PBT

**Clamp Nuts :** Galvanized Steel

**Face Material :** PBT

**Ground Clips :** Brass

**Grounding Screw :** Steel 8-32

**Line Contacts :** Brass Triple-Wipe

**Strap Material :** Steel

**Terminal Screws :** Brass 10-32

### Mechanical Specifications

**Product ID :** Ratings are permanently marked on device

### Product Features

**Color :** White

**Screw Terminal Torque** : 14-18 in-lbs

**Grade** : Heavy-Duty Industrial Specification Grade

**Terminal Accom.** : 14-10 AWG **NEMA** : 5-20R

**Terminal ID** : Brass-Hot, Green-Ground, Silver-Neutral

**Torque Range** : 14-16 inch pounds

Standards and Certifications

**ANSI** : C-73

**CSA C22.2 No. 42** : File 152105

**NEMA** : WD-1 & WD-6

**NOM** : 057

**UL Fed Spec WC-596** : File E13399

**UL498** : File E13399

**Warranty** : 10-Year Limited

**Patents** \*

CA2483480

MX257790

MX321216

US6743029

US8684771

This list is provided for patent marking purposes only. A good faith effort is made to maintain the accuracy and completeness of this list. No legal inference should be drawn from the omission of a patent from this list.

**SPECIFICATION SUBMITTAL**

<b>JOB NAME:</b> <input type="text"/>	<b>CATALOG NUMBERS:</b> <input type="text"/>	
<b>JOB NUMBER:</b> <input type="text"/>	<input type="text"/>	<input type="text"/>

**Leviton Manufacturing Co., Inc**

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S. T. Monday-Friday): +1-800-824-3005

**Leviton Manufacturing of Canada, Ltd.**

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 · FAX: +1-800-824-3005 · [www.leviton.com/canada](http://www.leviton.com/canada)

**Leviton S. de R.L. de C.V.**

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52) 5386- 1797 · [www.leviton.com.mx](http://www.leviton.com.mx)

Visit our Website at: [www.leviton.com](http://www.leviton.com)

© 2024 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

**Leviton has a global presence.**

If you would like to know where your local Leviton office is located please go to:  
[www.leviton.com/international/contacts](http://www.leviton.com/international/contacts)

**© 2024 Leviton Manufacturing Co., Inc.**