



Color:

Black-White

UPC Code: 078477795491

Country Of Origin: Mexico

#### **Available Colors:**







Black

# 4720-C

Locking Plug, 15 Amp, 125 Volt, Industrial Grade, Black & White

15 Amp, 125 Volt, NEMA L5-15P, 2P, 3W, Locking Plug, Industrial Grade, Grounding - Black/White

**ROHS Compliant:** Yes

Leviton's Black & White line of industrial grade plugs, connectors, flanged inlets, and outlets offer superior performance, long lasting reliability and features that are backed by a limited lifetime warranty:

- One piece contacts reduce friction and overheating
- Unique cord clamp accepts wide range of cord sizes (.245"-.700")
- Rugged nylon construction resists impact, sunlight, chemicals, and rough use
- Industry exclusive limited lifetime warranty
- Ideal for motor loads, such as shop vacs and pool pumps, and generators

#### **Technical Information**

**AC Horsepower Ratings** 

Horsepower Rating: 1/2 HP Amperage: 15 A

> **Current Interrupting:** Certified for current interrupting at full

**Electrical Specifications** 

rated current

**Dielectric Voltage:** 

Withstands 2000V per UL498

**Grounding:** Grounding

Pole: 2

Temperature Rise: Max 30C after 250 cycles OL at 200 percent rated current

Voltage: 125 VAC

Wire: 3

**Environmental Specifications** 

**Environment**: Dry

Flammability: Rated HB or

better UL94

Operating Temperature: -40°

C to 60°C

**Material Specifications** 

Assembly Screws: Steel, Zinc

Plated

**Back Cover:** Thermoplastic

Blades/Contacts: Solid Brass

Modified Nylon

Clamp Insert: Nylon Color: Black-White

**Body Material:** Impact

Cord-Clamp: Nylon

Terminal Screws: Brass

Brand: Black and White

Color: Black-White

**NEMA:** L5-15P

Wire Module: Nylon

**Product Features** 

# Mechanical Specifications

**Cord Range :** 0.230 to 0.685

**Product ID**: Ratings and NEMA I.D. permanently marked

on device

Terminal Accom.: 18-10 AWG

**Terminal ID**: Brass-Hot, Green-Ground, Silver-Neutral **Torque Range**: 10-14 in-lbs

Wire Gauge: 18-10 AWG

# Standards and Certifications

**ANSI:** C-73

CSA C22.2 No. 42 : File LR-406

NOM Certified: 057

UL Fed Spec WC-596: File

E13393

Warranty: Limited Lifetime

Warranty Warranty

# **Dimensional Drawing**



#### SPECIFICATION SUBMITTAL

JOB NAME:	CATALOG NUMBERS:
JOB NUMBER:	

# Leviton Manufacturing Co., Inc

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.

T. Monday-Friday): +1-800-824-3005

# Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 · FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52) 5386- 1797 · www.leviton.com.mx

# Visit our Website at: www.leviton.com

# Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to: www.leviton.com/international/contacts

© 2024 Leviton Manufacturing Co., Inc.