



**Color :**  White

**UPC Code :** 078477141311

**Country Of Origin :** Mexico

**NEMA :**  5-15R

**Available Colors :**



## 5262-SW

15 Amp Duplex Receptacle/Outlet, Industrial Grade, Self-Grounding

Duplex Receptacle Outlet, Heavy-Duty Industrial Specification Grade, Smooth Face, 15 Amp, 125 Volt, Back or Side Wire, NEMA 5-15R, 2-Pole, 3-Wire, Self-Grounding - White

**ROHS Compliant :** Yes

Leviton's line of Heavy-Duty Industrial Grade Receptacles are available with a number of wiring options and features. These heavy-duty receptacles are engineered for fine appearance and top performance in demanding commercial and institutional applications using a durable, thermoplastic face and impact-resistant construction.

### Technical Information

#### AC Horsepower Ratings

**At Rated Voltage :** 1/2 HP

#### Electrical Specifications

**Amperage :** 15 A

**Current Limiting :** Full Rated Current

**Dielectric Voltage :**  
Withstands 2000V per UL498

**Grounding :** Self-Grounding

**Pole :** 2

**Temperature Rise :** Max 30C  
after 250 cycles OL at 200  
percent rated current

**Voltage :** 125 VAC

**Wire :** 3

#### Environmental Specifications

**Flammability :** Rated V-2 per  
UL 94

**Operating Temperature :** -40°  
C to 60°C

#### Material Specifications

**Body Material :** Thermoplastic  
Nylon

**Clamp Nuts :** Galvanized Steel

**Color :** White

**Face Material :** Thermoplastic  
Nylon

**Ground Clips :** Brass

**Grounding Screw :** Steel 8-32

**Line Contacts :** Brass Triple-  
Wipe

**Strap Material :** Steel

**Terminal Screws :** Brass 10-32

#### Mechanical Specifications

#### Product Features

**Product ID :** Ratings are permanently marked on device

**Screw Terminal Torque :** 14-18 in-lbs

**Terminal Accom. :** 14-10 AWG

**Terminal ID :** Brass-Hot, Green-Ground, Silver-Neutral

**Termination :** Back or Side Wire

**Torque Range :** 14-16 inch pounds

**Body Material :** Thermoplastic Nylon

**Color :** White

**Device Type :** Duplex Receptacle Outlet

**Face Material :** Thermoplastic Nylon

**Feature 4 :** Smooth Face

**Grade :** Heavy-Duty Industrial Specification Grade

**Grounding :** Self-Grounding

**NEMA :** 5-15R

**Strap Material :** Steel

Standards and Certifications

**ANSI :** C-73

**CSA C22.2 No. 42 :** File 152105

**NEMA :** WD-1 & WD-6

**NOM :** 057

**UL Fed Spec WC-596 :** File E13399

**UL498 :** File E13399

**Warranty :** 2-Year Limited

**Patents\***

CA2483480

MX321216

US8684771

MX257790

US6743029

This list is provided for patent marking purposes only. A good faith effort is made to maintain the accuracy and completeness of this list. No legal inference should be drawn from the omission of a patent from this list.

**SPECIFICATION SUBMITTAL**

<b>JOB NAME:</b> <input type="text"/>	<b>CATALOG NUMBERS:</b> <input type="text"/>	<input type="text"/>
<b>JOB NUMBER:</b> <input type="text"/>	<input type="text"/>	<input type="text"/>

**Leviton Manufacturing Co., Inc**

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.

T. Monday-Friday): +1-800-824-3005

**Leviton Manufacturing of Canada, Ltd.**

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 ·  
FAX: +1-800-824-3005 · [www.leviton.com/canada](http://www.leviton.com/canada)

**Leviton S. de R.L. de C.V.**

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)  
5386- 1797 · [www.leviton.com.mx](http://www.leviton.com.mx)

**Visit our Website at: [www.leviton.com](http://www.leviton.com)**

© 2024 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without  
notice.

**Leviton has a global presence.**

If you would like to know where your local Leviton office is located please go to:  
[www.leviton.com/international/contacts](http://www.leviton.com/international/contacts)

**© 2024 Leviton Manufacturing Co., Inc.**