



#### Main

Product	Miniature circuit-breaker
Range	QO
Current Rating	15 A
Voltage Rating	120/240 V AC 240 V AC 120 V AC
Mounting Type	Plug-in
Number of Poles	3P
Circuit Breaker Type	Standard
Ratings	HACR rated
Electrical Connection	Pressure plate

#### Complementary

Interrupt Rating	10 KA 120/240 V AC 10 KA 240 V AC 10 kA 120 V AC
Number of Panel Spaces	3
Wire Size	AWG 14...AWG 8 copper or aluminium
Tightening Torque	35.4 lbf.in (4 N.m)
Height	3.0 in (76 mm)
Width	2.2 in (57 mm)
Depth	2.9 in (74 mm)
Net Weight	0.800 lb(US) (0.363 kg)

#### Environment

Certifications	UL Listed[RETURN]CSA
Ambient Rating	104 °F (40 °C)

#### Ordering and shipping details

Category	US1DE2A00012
Discount Schedule	DE2A
GTIN	785901400646
Returnability	Yes
Country of origin	MX

#### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.300 in (5.842 cm)
Package 1 Width	3.0000000000 in (7.62 cm)
Package 1 Length	3.200 in (8.128 cm)
Package 1 Weight	12.8 oz (363.0 g)
Unit Type of Package 2	BB1
Number of Units in Package 2	3
Package 2 Height	3.300 in (8.382 cm)
Package 2 Width	3.0000000000 in (7.62 cm)

Package 2 Length	6.800 in (17.272 cm)
Package 2 Weight	2.410 lb(US) (1.093 kg)
Unit Type of Package 3	CAR
Number of Units in Package 3	36
Package 3 Height	3.400 in (8.636 cm)
Package 3 Width	14.300 in (36.322 cm)
Package 3 Length	21.50 in (54.61 cm)
Package 3 Weight	30.60 lb(US) (13.88 kg)

### Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 <a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant with Exemptions
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	 <a href="#">China RoHS Declaration</a>
RoHS exemption information	 <a href="#">Yes</a>
Circularity Profile	No need of specific recycling operations
Halogen content performance	Halogen free product

### Contractual warranty

Warranty	18 months
----------	-----------