



Main

Product	Miniature circuit-breaker
Range	QO
Current Rating	30 A
Voltage Rating	120/240 V AC 240 V AC 120 V AC
Mounting Type	Plug-in
Number of Poles	3P
Circuit Breaker Type	Standard
Ratings	HACR rated
Electrical Connection	Pressure plate

Complementary

Interrupt Rating	10 KA 120/240 V AC 10 KA 240 V AC 10 kA 120 V AC
Number of Panel Spaces	3
Wire Size	AWG 14...AWG 8 copper or aluminium
Tightening Torque	35.4 lbf.in (4 N.m)
Height	3.0 in (76 mm)
Width	2.2 in (57 mm)
Depth	2.9 in (74 mm)
Net Weight	0.899 lb(US) (0.408 kg)

Environment

Certifications	UL Listed[RETURN]CSA
Ambient Rating	104 °F (40 °C)

Ordering and shipping details

Category	US1DE2A00012
Discount Schedule	DE2A
GTIN	785901400721
Returnability	Yes
Country of origin	IE

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.0000000000 in (7.62 cm)
Package 1 Width	2.200 in (5.588 cm)
Package 1 Length	3.300 in (8.382 cm)
Package 1 Weight	14.4 oz (408.0 g)
Unit Type of Package 2	BB1
Number of Units in Package 2	3
Package 2 Height	3.700 in (9.398 cm)
Package 2 Width	2.200 in (5.588 cm)

Package 2 Length	7.100 in (18.034 cm)
Package 2 Weight	2.551 lb(US) (1.157 kg)
Unit Type of Package 3	CAR
Number of Units in Package 3	36
Package 3 Height	3.700 in (9.398 cm)
Package 3 Width	14.400 in (36.576 cm)
Package 3 Length	21.700 in (55.118 cm)
Package 3 Weight	30.699 lb(US) (13.925 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes
Circularity Profile	No need of specific recycling operations
Halogen content performance	Halogen free product

Contractual warranty

Warranty	18 months
----------	-----------