



### Main

Product	Miniature circuit-breaker
Range	QO
Current Rating	70 A
Voltage Rating	120/240 V AC 240 V AC 120 V AC
Mounting Type	Plug-in
Number of Poles	3P
Circuit Breaker Type	Standard
Ratings	HACR rated
Electrical Connection	Box lugs

### Complementary

Interrupt Rating	10 KA 120/240 V AC 10 KA 240 V AC 10 kA 120 V AC
Number of Panel Spaces	3
Wire Size	AWG 8...AWG 2 copper or aluminium
Tightening Torque	49.6 lbf.in (5.6 N.m)
Height	3.1 in (79 mm)
Width	2.2 in (57 mm)
Depth	2.9 in (74 mm)
Net Weight	1.049 lb(US) (0.476 kg)

### Environment

Certifications	UL Listed[RETURN]CSA
Ambient Rating	104 °F (40 °C)

### Ordering and shipping details




Category	US1DE2A00012
Discount Schedule	DE2A
GTIN	785901004387
Returnability	Yes
Country of origin	US

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.300 in (5.842 cm)
Package 1 Width	3.400 in (8.636 cm)
Package 1 Length	3.800 in (9.652 cm)
Package 1 Weight	16.8 oz (476.0 g)
Unit Type of Package 2	PAL
Number of Units in Package 2	1728
Package 2 Height	40.0000000000 in (101.6 cm)
Package 2 Width	36.0000000000 in (91.44 cm)

Package 2 Length	48.0000000000 in (121.92 cm)
Package 2 Weight	1831.679 lb(US) (830.835 kg)
Unit Type of Package 3	CAR
Number of Units in Package 3	36
Package 3 Height	3.800 in (9.652 cm)
Package 3 Width	13.900 in (35.306 cm)
Package 3 Length	21.0000000000 in (53.34 cm)
Package 3 Weight	39.350 lb(US) (17.849 kg)

### Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Cadmium and cadmium compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	 <a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	 <a href="#">China RoHS Declaration</a>
RoHS exemption information	 <a href="#">Yes</a>
Circularity Profile	No need of specific recycling operations
Halogen content performance	Halogen free product

### Contractual warranty

Warranty	18 months
----------	-----------