QOB250

Mini circuit breaker, QO, 50A, 2 pole, 120/240VAC, 10kA, bolt on





Main

Product	Miniature circuit-breaker
Range	QO
Current Rating	50 A
Voltage Rating	120/240 V AC 120 V AC
Mounting Type	Bolt-on
Number of Poles	2P
Circuit Breaker Type	Standard
Ratings	HACR rated
Electrical Connection	Box lugs

Complementary

Interrupt Rating	10 KA 120/240 V AC	
	10 kA 120 V AC	
Number of Panel Spaces	2	
Wire Size	AWG 8AWG 2 copper or aluminium	
Tightening Torque	44.3 lbf.in (5 N.m)	
Height	3.1 in (79 mm)	
Width	1.5 in (38 mm)	
Depth	2.9 in (74 mm)	
Net Weight	0.549 lb(US) (0.249 kg)	

Environment

Certifications	UL Listed[RETURN]CSA
Ambient Rating	104 °F (40 °C)

Ordering and shipping details

Category	US10DE200015	
Discount Schedule	0DE2	
GTIN	785901416982	
Returnability	Yes	
Country of origin	US	

Packing Units

PCE
1
1.50 in (3.81 cm)
3.300 in (8.382 cm)
3.50 in (8.89 cm)
4.000 oz (113.398 g)
BB1
5
3.400 in (8.636 cm)
2.700 in (6.858 cm)

Package 2 Length	7.700 in (19.558 cm)
Package 2 Weight	2.961 lb(US) (1.343 kg)
Unit Type of Package 3	CAR
Number of Units in Package 3	50
Package 3 Height	8.100 in (20.574 cm)
Package 3 Width	7.600 in (19.304 cm)
Package 3 Length	17.200 in (43.688 cm)
Package 3 Weight	30.351 lb(US) (13.767 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Compliant with Exemptions
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	☑ China RoHS Declaration
RoHS exemption information	₫Yes
Circularity Profile	No need of specific recycling operations
Halogen content performance	Halogen free product

Contractual warranty

141	
Warranty	18 months
vvairanty	To months