



Main

Product	Miniature circuit-breaker
Range	QO
Current Rating	60 A
Voltage Rating	120/240 V AC 240 V AC 120 V AC
Mounting Type	Bolt-on
Number of Poles	3P
Circuit Breaker Type	Standard
Ratings	HACR rated
Electrical Connection	Box lugs

Complementary

Interrupt Rating	10 KA 120/240 V AC 10 KA 240 V AC 10 kA 120 V AC
Number of Panel Spaces	3
Wire Size	AWG 8...AWG 2 copper or aluminium
Tightening Torque	44.3 lbf.in (5 N.m)
Height	3.1 in (79 mm)
Width	2.2 in (57 mm)
Depth	2.9 in (74 mm)
Net Weight	0.851 lb(US) (0.386 kg)

Environment

Certifications	UL Listed[RETURN]CSA
Ambient Rating	104 °F (40 °C)

Ordering and shipping details

Category	US10DE200015
Discount Schedule	0DE2
GTIN	785901417187
Returnability	Yes
Country of origin	IE

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.300 in (8.382 cm)
Package 1 Width	3.000000000 in (7.62 cm)
Package 1 Length	3.50 in (8.89 cm)
Package 1 Weight	13.6 oz (386.0 g)
Unit Type of Package 2	BB1
Number of Units in Package 2	3
Package 2 Height	3.400 in (8.636 cm)
Package 2 Width	2.800 in (7.112 cm)

Package 2 Length	6.800 in (17.272 cm)
Package 2 Weight	2.590 lb(US) (1.175 kg)
Unit Type of Package 3	CAR
Number of Units in Package 3	36
Package 3 Height	3.300 in (8.382 cm)
Package 3 Width	14.200 in (36.068 cm)
Package 3 Length	21.700 in (55.118 cm)
Package 3 Weight	32.0001 lb(US) (14.515 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes
Circularity Profile	No need of specific recycling operations
Halogen content performance	Halogen free product

Contractual warranty

Warranty	18 months
----------	-----------