



Main

Product or Component Type	Miniature circuit-breaker
Range of Product	QOU
Circuit breaker type	Standard
Circuit breaker application	HACR rated

Complementary

Line Rated Current	30 A
Electrical connection	Slotted box lugs, line side Slotted box lugs, load side
[Ue] rated operational voltage	120/240 V AC 240 V AC 120 V AC 48 V DC
Mounting Mode	Unit mount
AWG gauge	AWG 14...AWG 2 aluminium/copper
Height	4.05 in (102.87 mm)
Width	2.25 in (57.15 mm)
Depth	2.95 in (74.93 mm)
Tightening torque	45 lbf.in (5.08 N.m) (AWG 14...AWG 2)

Environment

Product Certifications	CSA[RETURN]UL Listed[RETURN]IEC
------------------------	---------------------------------

Ordering and shipping details

Category	US10DE200900
Discount Schedule	0DE2
GTIN	785901418924
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.50 in (6.35 cm)
Package 1 Width	3.600 in (9.144 cm)
Package 1 Length	4.800 in (12.192 cm)
Package 1 Weight	17.600 oz (498.952 g)
Unit Type of Package 2	CAR
Number of Units in Package 2	20

Package 2 Height	3.50 in (8.89 cm)
Package 2 Width	13.400 in (34.036 cm)
Package 2 Length	20.50 in (52.07 cm)
Package 2 Weight	22.851 lb(US) (10.365 kg)
Unit Type of Package 3	PAL
Number of Units in Package 3	960
Package 3 Height	40.0000000000 in (101.6 cm)
Package 3 Width	40.0000000000 in (101.6 cm)
Package 3 Length	48.0000000000 in (121.92 cm)
Package 3 Weight	1086.0002 lb(US) (492.601 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes
Circularity Profile	No need of specific recycling operations
Halogen content performance	Halogen free product

Contractual warranty

Warranty	18 months
----------	-----------