QO816L100F

Load center, QO, 1 phase, 8 spaces, 16 circuits, 100A fixed main lugs, NEMA1, flush cover





Main

Marketing Trade Name	QO
Product Type	Load Center
Cover Type	Flush cover

Complementary

Tightening Torque	Main lugs 50 lb.in, AWG 8, aluminium/copper Main lugs 50 lb.in, AWG 6AWG 1/0, aluminium/copper	
PoN Convertible Mains (lugs)	Fixed Mains (lugs)	
Rated Current	100 A	
Number of Spaces	8	
Max Short Circuit Current Rating	10 kA	
Maximum Number of Single Pole Circuits	16	
Maximum Number of Tandem Breakers	8	
Number of Phases	1 phase 3 wires	
Voltage Rating	120/240 V AC	
Wire Size	AWG 8AWG 1 aluminium/copper	
Ground Bar	Grounding bar (ordered separately)	
Electrical Connection	Lugs	
Busbar Material	Tin plated aluminium: busbar	
Enclosure Material	Welded sheet steel	
Surface Finish	Baked enamel Gray	
Box Number	4	
Height	12.6 in (319 mm)	
Width	8.9 in (226 mm)	

Environment

Enclosure Rating	NEMA 1 indoor enclosure
Ambient Air Temperature for Operation	23 °F (-5 °C) 104 °F (40 °C)
Product Certifications	UL Listed

Ordering and shipping details

Discount Schedule DE3A GTIN 785901785675 Returnability Yes Country of origin US	Category	US1DE3A00101	
Returnability Yes	Discount Schedule	DE3A	
	GTIN	785901785675	
Country of origin US	Returnability	Yes	
	Country of origin	US	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.2 in (10.7 cm)
Package 1 Width	10.8 in (27.4 cm)
Package 1 Length	14.5 in (36.8 cm)
Package 1 Weight	7.83 lb(US) (3.55 kg)
Unit Type of Package 2	PAL
Number of Units in Package 2	78
Package 2 Height	35.0000000000 in (88.9 cm)
Package 2 Width	43.0000000000 in (109.22 cm)
Package 2 Length	48.0000000000 in (121.92 cm)
Package 2 Weight	633.569 lb(US) (287.382 kg)

Offer Sustainability

Sustainable offer status	Green Premium product	
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
REACh Regulation	REACh Declaration	
EU RoHS Directive	Compliant with Exemptions	
Mercury free	Yes	
China RoHS Regulation	China RoHS Declaration	
RoHS exemption information	₫Yes	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	No need of specific recycling operations	

Contractual warranty

Outifactual warranty		
Warranty	18 months	