


Series K050 Clear PVC Tubing

Utility grade non-toxic clear food grade PVC tubing for general use applications.



Item #	Temperature Range	Nominal I.D.	Nominal 2 O.D.	Max. Working Pressure at 70°F (20°C)	Standard Length	Approx. Weight
K050-0204X100	25 to 150 °F -4 to 65 °C	0.130 in 3.20 mm	0.250 in 6.40 mm	65 PSI	100 ft	2.00 lbs
K050-0305X100	25 to 150 °F -4 to 65 °C	0.190 in 4.80 mm	0.310 in 7.90 mm	55 PSI	100 ft	2.70 lbs
K050-0406X100	25 to 150 °F -4 to 65 °C	0.250 in 6.35 mm	0.380 in 9.50 mm	55 PSI	100 ft	3.40 lbs
K050-0408X100	25 to 150 °F -4 to 65 °C	0.250 in 6.35 mm	0.500 in 12.7 mm	60 PSI	100 ft	8.00 lbs
K050-0507X100	25 to 150 °F -4 to 65 °C	0.310 in 7.90 mm	0.440 in 11.1 mm	50 PSI	100 ft	4.00 lbs
K050-0608X100	25 to 150 °F -4 to 65 °C	0.380 in 9.50 mm	0.500 in 12.7 mm	45 PSI	100 ft	4.70 lbs
K050-0609X100	25 to 150 °F -4 to 65 °C	0.380 in 9.50 mm	0.560 in 14.3 mm	50 PSI	100 ft	7.50 lbs
K050-0610X100	25 to 150 °F -4 to 65 °C	0.380 in 9.50 mm	0.620 in 15.9 mm	55 PSI	100 ft	10.7 lbs
K050-0810X100	25 to 150 °F -4 to 65 °C	0.500 in 12.70 mm	0.620 in 15.9 mm	30 PSI	100 ft	6.00 lbs
K050-0812X100	25 to 150 °F -4 to 65 °C	0.500 in 12.70 mm	0.750 in 19.1 mm	45 PSI	100 ft	13.4 lbs
K050-1013X100	25 to 150 °F -4 to 65 °C	0.630 in 15.90 mm	0.810 in 20.6 mm	35 PSI	100 ft	11.6 lbs
K050-1014X100	25 to 150 °F -4 to 65 °C	0.630 in 15.90 mm	0.880 in 22.2 mm	40 PSI	100 ft	16.1 lbs
K050-1216X100	25 to 150 °F -4 to 65 °C	0.750 in 19.00 mm	1.000 in 25.4 mm	35 PSI	100 ft	18.8 lbs
K050-1418X100	25 to 150 °F -4 to 65 °C	0.880 in 22.20 mm	1.120 in 28.6 mm	30 PSI	100 ft	21.4 lbs
K050-1620X100	25 to 150 °F -4 to 65 °C	1.000 in 25.40 mm	1.250 in 31.8 mm	25 PSI	100 ft	24.1 lbs
K050-2024X50	25 to 150 °F -4 to 65 °C	1.250 in 31.80 mm	1.500 in 38.1 mm	20 PSI	50 ft	14.8 lbs
K050-2430X50	25 to 150 °F -4 to 65 °C	1.500 in 38.10 mm	1.880 in 47.6 mm	30 PSI	50 ft	27.1 lbs
K050-2432X50	25 to 150 °F -4 to 65 °C	1.500 in 38.10 mm	2.000 in 50.8 mm	35 PSI	50 ft	37.5 lbs
K050-3240X50	25 to 150 °F -4 to 65 °C	2.000 in 50.80 mm	2.500 in 63.5 mm	35 PSI	50 ft	48.2 lbs