

POLYWIRE® Series K7130 Heavy Wall PVC Food & Beverage Vacuum/Transfer Hose

Heavy wall food and beverage grade vacuum/transfer hose with rated working pressures.



Item #	Temp. Range	Nominal I.D.	Nominal O.D.	Max. Working Pressure at 70°F (20°C)	Max. Working 2 Pressure at 122°F (50°C)	Standard Length	Approx. Weight
K7130-04X50	25 to 150 °F -4 to 65 °C	0.250 in 6.35 mm	0.500 in 12.7 mm	250 PSI	80 PSI	50 ft	5.00 lbs
K7130-04X100	25 to 150 °F -4 to 65 °C	0.250 in 6.35 mm	0.500 in 12.7 mm	250 PSI	80 PSI	100 ft	10.0 lbs
K7130-06X50	25 to 150 °F -4 to 65 °C	0.380 in 9.50 mm	0.620 in 15.9 mm	150 PSI	80 PSI	50 ft	6.50 lbs
K7130-06X100	25 to 150 °F -4 to 65 °C	0.380 in 9.50 mm	0.620 in 15.9 mm	150 PSI	80 PSI	100 ft	13.0 lbs
K7130-08X50	25 to 150 °F -4 to 65 °C	0.500 in 12.70 mm	0.810 in 20.7 mm	150 PSI	80 PSI	50 ft	10.5 lbs
K7130-08X100	25 to 150 °F -4 to 65 °C	0.500 in 12.70 mm	0.810 in 20.7 mm	150 PSI	80 PSI	100 ft	21.0 lbs
K7130-10X50	25 to 150 °F -4 to 65 °C	0.630 in 15.90 mm	1.000 in 25.4 mm	150 PSI	65 PSI	50 ft	15.0 lbs
K7130-10X100	25 to 150 °F -4 to 65 °C	0.630 in 15.90 mm	1.000 in 25.4 mm	150 PSI	65 PSI	100 ft	30.0 lbs
K7130-12X50	25 to 150 °F -4 to 65 °C	0.750 in 19.00 mm	1.120 in 28.6 mm	150 PSI	65 PSI	50 ft	18.0 lbs
K7130-12X100	25 to 150 °F -4 to 65 °C	0.750 in 19.00 mm	1.120 in 28.6 mm	150 PSI	65 PSI	100 ft	36.0 lbs
K7130-16X50	25 to 150 °F -4 to 65 °C	1.000 in 25.40 mm	1.380 in 34.9 mm	100 PSI	45 PSI	50 ft	22.0 lbs
K7130-16X100	25 to 150 °F -4 to 65 °C	1.000 in 25.40 mm	1.380 in 34.9 mm	100 PSI	45 PSI	100 ft	44.0 lbs
K7130-20X50	25 to 150 °F -4 to 65 °C	1.250 in 31.80 mm	1.750 in 44.5 mm	100 PSI	50 PSI	50 ft	37.0 lbs
K7130-20X25	25 to 150 °F -4 to 65 °C	1.250 in 31.80 mm	1.750 in 44.5 mm	100 PSI	50 PSI	25 ft	18.5 lbs
K7130-24X25	25 to 150 °F -4 to 65 °C	1.500 in 38.10 mm	2.000 in 50.8 mm	100 PSI	35 PSI	25 ft	21.0 lbs
K7130-24X50	25 to 150 °F -4 to 65 °C	1.500 in 38.10 mm	2.000 in 50.8 mm	100 PSI	35 PSI	50 ft	42.0 lbs
K7130-32X25	25 to 150 °F -4 to 65 °C	2.000 in 50.80 mm	2.500 in 63.5 mm	100 PSI	35 PSI	25 ft	28.00 lbs
K7130-32X50	25 to 150 °F -4 to 65 °C	2.000 in 50.80 mm	2.500 in 63.5 mm	100 PSI	35 PSI	50 ft	56.0 lbs