

Series K1154, K1156 General Purpose PVC Air & Water Hose

A general purpose PVC air and water hose for in plant and outdoor applications in temperate climate conditions.

***Note :** Series K1156 5/16" ID size is a non stock item.



Item #	Temp.	Nominal	Nominal 2	Max. Working	Max. Working	Standard	Approx.	Color
	Range	I.D.	O.D.	Pressure	Pressure 2	Length	Weight	
				at 70°F (20°C)	at 122°F (50°C)			
K1154-04X100	14 to 150 °F -10 to 65 °C	0.250 in 6.35 mm	0.500 in 12.7 mm	300 PSI	150 PSI	100 ft	8.00 lbs	Red
K1154-04X500	14 to 150 °F -10 to 65 °C	0.250 in 6.35 mm	0.500 in 12.7 mm	300 PSI	150 PSI	500 ft	44.0 lbs	Red
K1154-05X100	14 to 150 °F -10 to 65 °C	0.310 in 7.90 mm	0.620 in 15.9 mm	300 PSI	150 PSI	100 ft	13.0 lbs	Red
K1154-05X500	14 to 150 °F -10 to 65 °C	0.310 in 7.90 mm	0.620 in 15.9 mm	300 PSI	150 PSI	500 ft	68.0 lbs	Red
K1154-06X100	14 to 150 °F -10 to 65 °C	0.380 in 9.50 mm	0.620 in 15.9 mm	300 PSI	150 PSI	100 ft	11.0 lbs	Red
K1154-06X500	14 to 150 °F -10 to 65 °C	0.380 in 9.50 mm	0.620 in 15.9 mm	300 PSI	150 PSI	500 ft	56.0 lbs	Red
K1154-08X100	14 to 150 °F -10 to 65 °C	0.500 in 12.70 mm	0.750 in 19.1 mm	300 PSI	150 PSI	100 ft	14.0 lbs	Red
K1154-08X500	14 to 150 °F -10 to 65 °C	0.500 in 12.70 mm	0.750 in 19.1 mm	300 PSI	150 PSI	500 ft	77.0 lbs	Red
K1154-10X100	14 to 150 °F -10 to 65 °C	0.630 in 15.90 mm	0.860 in 22.6 mm	200 PSI	100 PSI	100 ft	18.0 lbs	Red
K1154-10X300	14 to 150 °F -10 to 65 °C	0.630 in 15.90 mm	0.860 in 22.6 mm	200 PSI	100 PSI	300 ft	60.0 lbs	Red
K1154-12X100	14 to 150 °F -10 to 65 °C	0.750 in 19.00 mm	1.030 in 26.2 mm	200 PSI	75 PSI	100 ft	22.0 lbs	Red
K1154-12X300	14 to 150 °F -10 to 65 °C	0.750 in 19.00 mm	1.030 in 26.2 mm	200 PSI	75 PSI	300 ft	72.0 lbs	Red
K1154-16X100	14 to 150 °F -10 to 65 °C	1.000 in 25.40 mm	1.310 in 33.3 mm	150 PSI	75 PSI	100 ft	31.0 lbs	Red
K1154-16X300	14 to 150 °F -10 to 65 °C	1.000 in 25.40 mm	1.310 in 33.3 mm	150 PSI	75 PSI	300 ft	105 lbs	Red
K1156-04X100	14 to 150 °F -10 to 65 °C	0.250 in 6.35 mm	0.500 in 12.7 mm	300 PSI	150 PSI	100 ft	8.00 lbs	Blue
K1156-04X500	14 to 150 °F -10 to 65 °C	0.250 in 6.35 mm	0.500 in 12.7 mm	300 PSI	150 PSI	500 ft	44.0 lbs	Blue
*K1156-05X100	14 to 150 °F -10 to 65 °C	0.310 in 7.90 mm	0.620 in 15.9 mm	300 PSI	150 PSI	100 ft	13.0 lbs	Blue
*K1156-05X500	14 to 150 °F	0.310 in	0.620 in	300 PSI	150 PSI	500 ft	68.0 lbs	Blue

05X500	-10 to 65 °C	7.90 mm	15.9 mm					
K1156-	14 to 150 °F	0.380 in	0.620 in	300 PSI	150 PSI	100 ft	11.0 lbs	Blue
06X100	-10 to 65 °C	9.50 mm	15.9 mm					
K1156-	14 to 150 °F	0.380 in	0.620 in	300 PSI	150 PSI	500 ft	56.0 lbs	Blue
06X500	-10 to 65 °C	9.50 mm	15.9 mm					
K1156-	14 to 150 °F	0.500 in	0.750 in	300 PSI	150 PSI	100 ft	14.0 lbs	Blue
08X100	-10 to 65 °C	12.70 mm	19.1 mm					
K1156-	14 to 150 °F	0.500 in	0.750 in	300 PSI	150 PSI	500 ft	77.0 lbs	Blue
08X500	-10 to 65 °C	12.70 mm	19.1 mm					
K1156-	14 to 150 °F	0.630 in	0.860 in	200 PSI	100 PSI	100 ft	18.0 lbs	Blue
10X100	-10 to 65 °C	15.90 mm	22.6 mm					
K1156-	14 to 150 °F	0.630 in	0.860 in	200 PSI	100 PSI	300 ft	60.0 lbs	Blue
10X300	-10 to 65 °C	15.90 mm	22.6 mm					
K1156-	14 to 150 °F	0.750 in	1.030 in	200 PSI	75 PSI	100 ft	22.0 lbs	Blue
12X100	-10 to 65 °C	19.00 mm	26.2 mm					