



Accuflex Industrial Hose, Ltd.

36663 Van Born Road, Suite 300

Romulus, MI 48174

Phone: (734) 713-4100 • **Fax:** (734) 713-4190

Email: sales@accuflex.com • **Website:** www.accuflex.com

[Accuflex Products](#)

[Beverage, LP Gas, and Medical](#) > [Series HSC2840 Blue Tint, HSC2841 Yellow, HSC2844 Red, HSC2846 Blue Polyurethane Self-Store Tubing & Reinforced Hose](#) > Item # HSC2840-04x10

Item # HSC2840-04x10, Series HSC2840 Blue Tint, HSC2841 Yellow, HSC2844 Red, HSC2846 Blue Polyurethane Self-Store Tubing & Reinforced Hose



[larger image](#)

Series HSC2840 Blue Tint, HSC2841 Yellow, HSC2844 Red, HSC2846 Blue Polyurethane Self-Store Tubing & Reinforced Hose

Ether based polyurethane self-store coiled tubing & hose assemblies for air tool service.

- Standard assemblies have 4" pigtail and 20" whip end.
- Permanent crimped male swivel brass fittings provide greater strength and pull-out resistance . . . rubber bend restrictors over fittings prevents scratches and scuffs.

Note : Not recommended for transfer of brake fluids.

[Features](#) · [Applications](#) · [Specifications](#)



Features

- Offers strength with flexibility, highly kink-resistant
- Light weight (up to 15% lighter than our previous design), easy to use - helps to reduce worker fatigue
- Highly abrasion-resistant and non-marking
- Superior oil resistance - complies with RMA's Class A designation for high oil resistance
- Reinforcement - high tensile strength yarn reinforcement provides increased working pressure (HSC2950 only)
- Standard tubing/hose assemblies have 4" pigtail and 20" whip end
- Permanent crimped male swivel brass fittings provide greater strength and pull-out resistance . . . heat shrink tubing over fittings prevents scratches and scuffs
- Good resistance to hydrolysis and algae growth in warm water applications
- Silicone-free


Applications

- Assembly line air tools and work stations
- Automotive repair and body shops
- Transfer of air, fluids and chemicals
- Transparent blue tint (HSC2840) allows monitoring of flow
- Car wash soap dispensers
- Not recommended for transfer of brake fluids.

Specifications

Series	HSC2840
Size Code x Length	04 x 10
Temperature Range	-40 to 175 °F -40 to 80 °C
Nominal ID Size	1/4 Inches 6.35 mm
Nominal OD Size	0.375 Inches 9.5 mm
Max. Working Pressure at 70°F (20°C) 	125 PSI
Max. Working Pressure at 122°F (50°C) 	75 PSI
Working Length	8 ft.
Approx. Weight	5.0 lbs
Coil OD	2 Inches
Color	Blue Tint
Brand	Kuri Tec ®
Standard Package	10

Application / Material Conveyed	Air Lines, Assembly Applications Air Lines, low Temperature Automotive Repair and Body Shops Car Wash Applications Car Wash Soap Dispensers Monitoring of Flow Pneumatic Air Lines Transfer of Air, Fluids and Chemicals
---------------------------------	---

Legend Notes Click on question mark icons ()for additional information.

