


Female Coupling



66SA - Compression x Female Pipe These products contain lead and are not allowed by Federal Law to be installed for potable water use in the U.S.A. and its territories. **WARNING:** Furthermore, these products contain a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.

Name	Temperature	Thread Size	Weight Per 1
00266-0202	- 65 to +250	5/16-24	3
00266-0302	- 65 to +250	5/16-24 3/8-24	3
00266-0304	- 65 to +250	3/8-24 7/16-24	4
00266-0402	- 65 to +250	5/16-24 7/16-24	5
00266-0404	- 65 to +250	7/16-24	6
00266-0406	- 65 to +250	7/16-24 9/16-24	8
00266-0408	- 65 to +250	7/16-24 11/16-20	10
00266-0502	- 65 to +250	5/16-24 1/2-24	6
00266-0504	- 65 to +250	7/16-24 1/2-24	7
00266-0506	- 65 to +250	9/16-24 1/2-24	8
00266-0602	- 65 to +250	5/16-24 9/16-24	7
00266-0604	- 65 to +250	7/16-24 9/16-24	8
00266-0606	- 65 to +250	9/16-24	10
00266-0608	- 65 to +250	11/16-20 9/16-24	13
00266-0612	- 65 to +250	1-18 9/16-24	17
00266-0804	- 65 to +250	7/16-24 11/16-20	10
00266-0806	- 65 to +250	11/16-20 9/16-24	14
00266-0808	- 65 to +250	11/16-20	16
00266-0812	- 65 to +250	11/16-20 1-18	23
00266-1006	- 65 to +250	13/16-18 9/16-24	20
00266-1008	- 65 to +250	11/16-20 13/16-18	23
00266-1012	- 65 to +250	13/16-18 1-18	26
00266-1208	- 65 to +250	11/16-20 1-18	26
00266-1212	- 65 to +250	1-18	30
00266-1408	- 65 to +250	11/16-20 1 1/8-18	34
00266-1412	- 65 to +250	1-18 1 1/8-18	38