

Female Coupling



406 - Flare x Female Pipe These products contain lead and are not allowed by Federal Law to be installed for potable water use in the U.S.A. and its territories. **WARNING:** Furthermore, these products contain a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.

Name	Temperature	Thread Size	Weight Per 1
04046-0202	- 65 to +250	5/16-24	2
04046-0302	- 65 to +250	5/16-24 3/8-24	3
04046-0402	- 65 to +250	5/16-24 7/16-20	4
04046-0404	- 65 to +250	7/16-20	5
04046-0406	- 65 to +250	7/16-20 5/8-18	6
04046-0408	- 65 to +250	7/16-20 3/4-16	8
04046-0502	- 65 to +250	5/16-24 1/2-20	4
04046-0504	- 65 to +250	7/16-20 1/2-20	5
04046-0506	- 65 to +250	1/2-20 5/8-18	6
04046-0508	- 65 to +250	1/2-20 3/4-16	8
04046-0602	- 65 to +250	5/16-24 5/8-18	7
04046-0604	- 65 to +250	7/16-20 5/8-18	9
04046-0606	- 65 to +250	5/8-18	10
04046-0608	- 65 to +250	5/8-18 3/4-16	13
04046-0612	- 65 to +250	5/8-18 1 1/16-14	16
04046-0804	- 65 to +250	7/16-20 3/4-16	10
04046-0806	- 65 to +250	5/8-18 3/4-16	11
04046-0808	- 65 to +250	3/4-16	14
04046-0812	- 65 to +250	3/4-16 1 1/16-14	18
04046-1006	- 65 to +250	5/8-18 7/8-14	22
04046-1008	- 65 to +250	3/4-16 7/8-14	23
04046-1012	- 65 to +250	7/8-14 1 1/16-14	26
04046-1208	- 65 to +250	3/4-16 1 1/16-14	31
04046-1212	- 65 to +250	1 1/16-14	38
04046-1412	- 65 to +250	1 1/4-12 1 1/16-14	47