

Saint Ferrer™ Gasket Products


Rubber Series Style SF70

Technical Data Sheet

Series Description

The consistent quality of Saint Ferrer™ Rubber Series gasket materials make them suitable for low, moderate and highly aggressive applications.

Physical Properties	
Material	SBR ASTM D1330 Grade 2
Color	Red
Max temp (°F)	180
Continuous temp (°F)	N/A
Max pressure (psi)	250
Continuous pressure (psi)	N/A
Compressibility (%)	N/A
Min recovery (%)	N/A
Tensile Strength (psi)	800
Min Elongation(%)	200
Hardness (Shore A)	75 +/- 5
Dielectric Strength , 1/16" thick material (V/mil)	N/A
B16.5 gasket group	1a
PxT value 1/8" thick	20000
Gasket constants Gb,a,Gs	--
Notes	E
Notes on Compatible Media	
E - General purpose air and water	



Disclaimer of Accuracy or Quality: Westermann Bolting Technology Co. makes no warranty, express or implied, and does not assume any legal liability or responsibility for the accuracy or completeness of any information contained on, or derived from this sheet. This information is for the purpose of supporting selection and should be interpreted only by a licensed professional engineer with piping design experience.

© 2012 Westermann Bolting Technology Co. All rights reserved