



Circle Valve Technologies Inc.

1533 Gehman Road
Harleysville, PA 19438

Toll Free: **800-645-6733** | Phone: **267-933-6300** | Fax: **267-933-6305**
email: **sales@circlevalve.com**


Item # D559B-4M, Popoff Valves

List Price \$47.20

Features

- Popoff or inline valves
- Adjustable crack pressure
- Zero leakage
- Optional factory preset
- Accurate set pressure
- Wide range of cracking pressure
- Tamper-proof adjustment
- 100% seat leakage tested
- PED certifications and CE marking available for most models

Note: Proper filtration is recommended to prevent damage to sealing surface.
'D' Variation: Prefixed part number is supplied with a cap which diverts high pressure blasts from personnel and instruments, and serves as a rain and dust shield.



[SPECIFICATIONS](#) · [LEAKAGE](#) · [APPLICATIONS](#) · [SAFETY](#)

SPECIFICATIONS

Series	500
Operating Pressure	0.5 to 150 psig 0 to 10 bar
Variation	Popoff with deflector cap
Body Material	Brass

Seal Material ¹	Buna N
Valve Size	1/2 in
End Connection	Pipe Thread Male
Cracking Pressure	0.5 to 150 psig
Cracking Pressure Tolerance	±5%
Operating Temperature	-65 to 275 °F
Dim. L	1.98 in
Dim. L1	1.74 in
Hex	1 in
Dia. D (max.)	1.45 in
Weight	.23 lbs

1 520 Series: -100° F to +400° F (-73°C to +204°C) Teflon® o-ring
K520 Series: -320° F to +165° F (-196°C to +74°C) Polished Teflon® o-ring, cryogenic testing and serialization
580 Series: Polished Teflon® o-ring

LEAKAGE

Leakage, Ascending Pressure

Standard seals: 0 to 95% of cracking pressure

Silicon &EPR: 0 to 80% of cracking pressure

Teflon®:

Cracking pressures up to 2.4 psi: 4cc/min at 0 to 50% of cracking pressure Cracking pressures 2.5 psi and higher: 1cc/min at 0 to reseal pressure, 10cc/min from reseal to 90% of cracking pressures

Leakage at Reseat Pressure

All elastomeric seals: Zero

Teflon®: 1cc/min for cracking pressures 2.5 psi and higher

APPLICATIONS

- System overpressure protection
- Storage tanks
- Freon® recovery systems
- Medical equipment
- Refrigeration & heating equipment
- Measuring & dispensing pumps
- Communications equipment
- Process control instruments
- R&D pilot plants
- Vacuum pump safety

SAFETY

For Your Safety

It is solely the responsibility of the system designer and user to select products suitable for their specific application requirements and to ensure proper installation, operation, and maintenance of these products. Material compatibility, product ratings and application details should be considered in the selection. Improper selection or use of products described herein can cause personal injury or property damage.