


aqualtherm ELECTROFUSION COUPLING



Part no.	Dimension (ND — OD)	d	l	h	D	Weight
		[in]	[in]	[in]	[in]	[lb]
0117208	½" — 20 mm	0.79	1.38	1.42	1.24	0.11
0117210	¾" — 25 mm	0.98	1.54	1.52	1.44	0.13
0117212	1" — 32 mm	1.26	1.57	1.67	1.77	0.17
0117214	1 ¼" — 40 mm	1.57	1.81	1.85	2.13	0.23
0117216	1 ½" — 50 mm	1.97	2.03	2.05	2.56	0.31
0117218	2" — 63 mm	2.48	2.32	2.28	3.21	0.53
0117220	2 ½" — 75 mm	2.95	2.56	2.54	3.78	0.77
0117222	3" — 90 mm	3.54	2.85	2.83	4.47	1.10
0117224	3 ½" — 110 mm	4.33	3.15	3.25	5.47	1.81
0117226	4" — 125 mm	4.92	3.39	3.54	6.14	2.42
0117230 ^a	6" — 160 mm	6.30	3.66	4.31	7.76	3.87
0117234 ^a	8" — 200 mm	7.87	4.13	5.28	9.57	7.99
0117238 ^a	10" — 250 mm	9.84	4.92	6.69	12.4	15.8

^a Cannot be used in conjunction with UV pipe.