

ABS Low VOC Cements



ABS cements are specially formulated for rigid ABS pipe and fittings in all classes, schedules and fittings having interference type sockets. These medium-bodied, fast setting cements are used for all classes and schedules with interference fit through 8" diameter in ABS drain, waste and vent systems (DWV), and sewer applications. Do not use primer on ABS pipe and fittings.

- Low VOC emissions comply with *SCAQMD Rule 1168/316A*
- 3-Year Shelf Life



ABS-73 BLACK: Medium bodied, fast setting, high strength ABS solvent cement for all classes and schedules of pipe and fittings with interference fit through 8" diameter. Listings: ASTM D2235, NSF®-DWV, SW, U.P. Code.

ABS-73 Black Medium Body ABS Cement

Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
ABS73B-005	1/4 Pint	24	0	708	6.91
ABS73B-010	1/2 Pint	24	0	708	9.31
ABS73B-020	Pint	12	0	708	15.53
ABS73B-030	Quart	12	0	708	25.43
ABS73B-040	Gallon	6	0	708	85.27



ABS-71 YELLOW/MILKY: Medium bodied, fast setting, high strength ABS solvent cement for all classes and schedules of pipe and fittings with interference fit through 8" diameter. Listings: ASTM D2235, NSF®-DWV, SW, U.P. Code, CSA (Yellow Only) B181.1.

ABS-71 Yellow Medium Body ABS Cement

Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
ABS71Y-005	1/4 Pint	24	0	708	8.21
ABS71Y-010	1/2 Pint	24	0	708	9.81
ABS71Y-020	Pint	12	0	708	17.23
ABS71Y-030	Quart	12	0	708	29.36
ABS71Y-040	Gallon	6	0	708	99.89



ABS-71 Milky Medium Body ABS Cement

Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
ABS71M-005	1/4 Pint	24	0	708	8.21
ABS71M-010	1/2 Pint	24	0	708	9.81
ABS71M-020	Pint	24	0	708	17.23
ABS71M-030	Quart	24	0	708	29.36
ABS71M-040	Gallon	24	0	708	99.89