

SPRING CHECK VALVES



SPRING CHECK VALVES- PVC – SERIES 1001, 1002, 1011, 1012

Rated @ 200 PSI Static Pressure @ 72°F

	Part No.	Ref No.	Spring Tension	IPS Size Connection	Body Length	Color	Pkg. Qty.	Case (lbs.)	Product Class	Specifications
FPT x FPT EPDM Gasket 	1001-05	KC-0500-T	½ lb.	½"	4⅞"	White	20	4.5	41CV	PVC
	1001-07	KC-0750-T	½ lb.	¾"	4⅞"	White	20	4.5	41CV	NSF/ANSI
	1001-10	KC-1000-T	½ lb.	1"	5¼"	White	20	8.5	41CV	61+372
	1001-12	KC-1250-T	½ lb.	1¼"	6⅜"	White	15	12.0	41CV	
	1001-15	KC-1500-T	½ lb.	1½"	6⅜"	White	15	13.0	41CV	
	1001-20	KC-2000-T	½ lb.	2"	7"	White	10	15.5	41CV	
	1001-25		½ lb.	2½"	8⅝"	White	8	26.0	41CV	
	1001-30		½ lb.	3"	8⅝"	White	8	26.0	41CV	
	1002-05		2 lb.	½"	4⅞"	White	20	4.5	41CV	
	1002-07	KC2-0750-T	2 lb.	¾"	4⅞"	White	20	4.5	41CV	
	1002-10	KC2-1000-T	2 lb.	1"	5¼"	White	20	8.5	41CV	
	1002-12	KC2-1250-T	2 lb.	1¼"	6⅜"	White	15	12.0	41CV	
	1002-15	KC2-1500-T	2 lb.	1½"	6⅜"	White	15	13.0	41CV	
	1002-20	KC2-2000-T	2 lb.	2"	7"	White	10	16.0	41CV	
	1002-25		2 lb.	2½"	8⅝"	White	8	26.0	41CV	
	1002-30		2 lb.	3"	8⅝"	White	8	26.0	41CV	
SxS EPDM Gasket 	1011-05-025		¼lb.	½"	4⅞"	White	20	4.0	41CV	PVC
	1011-07-025		¼lb.	¾"	4⅞"	White	20	4.5	41CV	NSF/ANSI
	1011-05	KC-0500-S	¼lb.	½"	4⅞"	White	20	4.0	41CV	61+372
	1011-07	KC-0750-S	¼lb.	¾"	4⅞"	White	20	4.5	41CV	
	1011-10	KC-1000-S	¼lb.	1"	5¼"	White	20	8.5	41CV	
	1011-12	KC-1250-S	¼lb.	1¼"	6⅜"	White	15	12.0	41CV	
	1011-15	KC-1500-S	¼lb.	1½"	6⅜"	White	15	13.5	41CV	
	1011-20	KC-2000-S	¼lb.	2"	7"	White	10	16.0	41CV	
	1011-25		¼lb.	2½"	8⅝"	White	8	26.0	41CV	
	1011-30		¼lb.	3"	8⅝"	White	8	26.0	41CV	
	1012-05	KC2-0500-S	2 lb.	½"	4⅞"	White	20	4	41CV	
	1012-07	KC2-0750-S	2 lb.	¾"	4⅞"	White	20	4.5	41CV	
	1012-10	KC2-1000-S	2 lb.	1"	5¼"	White	20	8.5	41CV	
	1012-12	KC2-1250-S	2 lb.	1¼"	6⅜"	White	15	12.0	41CV	
	1012-15	KC2-1500-S	2 lb.	1½"	6⅜"	White	15	13.5	41CV	
	1012-20	KC2-2000-S	2 lb.	2"	7"	White	10	16.0	41CV	
	1012-25		2 lb.	2½"	8⅝"	White	8	26.0	41CV	
	1012-30		2 lb.	3"	8⅝"	White	8	26.0	41CV	
	1015-25		5 lb.	2½"	8⅝"	White	8	26.0	41CV	
	1015-30		5 lb.	3"	8⅝"	White	8	26.0	41CV	
SxS Clear PVC EPDM Gasket 	1011C10	KCC-1000-S	½ lb.	1"	5¼"	Clear	20	8.5	41CV	Clear PVC
	1011C12	KCC-1250-S	½ lb.	1¼"	6⅜"	Clear	15	12.0	41CV	NSF/ANSI
	1011C15	KCC-1500-S	½ lb.	1½"	6⅜"	Clear	15	13.5	41CV	61+372
	1011C20	KCC-2000-S	½ lb.	2"	7"	Clear	10	16.0	41CV	
	1012C12		2 lb.	1¼"	6⅜"	Clear	15	12.0	41CV	

	Part No.	Spring Tension	IPS Size & Connection	Body Length	Color	Pkg. Qty.	Case (lbs.)	Product Class	Specifications
	1700-07	½ lb.	¾" S x S	6.12"	White	20	9.8	41CV	Rated @ 200 PSI static pressure @ 72°F NSF/ANSI 61+372
	1700-10	½ lb.	1" S x S	6.83"	White	20	14.0	41CV	
	1700-15	½ lb.	1½" S x S	8.345"	White	12	19.8	41CV	
	1700-20	½ lb.	2" S x S	9.735"	White	12	22.9	41CV	
	1702-15	2 lb.	1½" S x S	8.35"	White	12	19.8	41CV	
	1702-20	2 lb.	2" S x S	9.74"	White	12	22.9	41CV	
	1700C07	½ lb.	¾" S x S	6.12"	Clear	20	9.8	41CV	Clear body with white nut and tailpiece Rated @ 200 PSI static pressure @ 72°F NSF/ANSI 61+372
	1700C10	½ lb.	1" S x S	6.83"	Clear	20	14.0	41CV	
	1700C15	½ lb.	1½" S x S	8.345"	Clear	12	19.8	41CV	
	1700C20	½ lb.	2" S x S	9.735"	Clear	12	22.9	41CV	
	1700C25	½ lb.	2½" S x S	12.625"	Clear	6	33.7	41CV	
	1700C30	½ lb.	3" S x S	12.625"	Clear	6	33.7	41CV	
	1702C15	2 lb.	1½" S x S	8.35"	Clear	12	19.8	41CV	
	1702C20	2 lb.	2" S x S	9.74"	Clear	12	22.9	41CV	
	1790-15	½ lb.	1½" S x S	6.540"	White	15	14.0	41CV	Rated @ 200 PSI static pressure @ 72°F, NSF/ANSI 61+372
	1790-20	½ lb.	2" S x S	7.350"	White	10	13.0	41CV	
	1790C15	½ lb.	1½" S x S	6.540"	Clear	15	14.5	41CV	Rated @ 200 PSI static pressure @ 72°F, Clear body with white nut and tail-piece NSF/ANSI 61+372
	1790C20	½ lb.	2" S x S	7.350"	Clear	10	14.5	41CV	
	1795C20	5 lb.	2" S x S	7.350"	Clear	10	14.5	41CV	
	1901-15	1 lb.	1½" S x S	5"	Tan	12	9	41CV	Rated @ 160 PSI static pressure @ 72°F
	1903-15	3 lb.	1½" S x S	5"	Tan	12	9	41CV	
	1901-20	1 lb.	2" S x 2½" Spg	5½"	Tan	12	14	41CV	
	1903-20	3 lb.	2" S x 2½" Spg	5½"	Tan	12	14	41CV	
	1091-20	½ lb.	2" S x S	5"	White	12	6.9	41CV	Non-Adjustable EPDM Seal Rated @ 200 PSI static pressure at 72°F NSF/ANSI 61+372
	1095-20	5 lb.	2" S x S	5"	White	12	6.9	41CV	
	1136-07	½ lb.	¾" MHT x ¾" FHT	4 ⅞"	White	20	4.5	41CV	Rated @ 200 PSI static pressure at 72°F NSF/ANSI 61+372
	1136-07-05	5 lb.	¾" MHT x ¾" FHT	4 ⅞"	White	20	4.5	41CV	

SPRING CHECK VALVES



SPA SPRING CHECK VALVES

	Part No.	Body Length	Color	Pkg. Qty.	Case (lbs.)	Product Class	Specifications
Versa Drain 	107015BK	4"	Black	12	7.6	41CV	Drain for portable spa
	1071GH	2.94"	Garden Hose Adpt.	1	—	41CV	

	Part No.	Spring Tension	IPS Size & Connection	Body Length	Color	Pkg. Qty.	Case (lbs.)	Product Class	Specifications
Spa Check Valve 	104732M	½ lb.	32mm	3 ¾"	White	20	5.0	41CV	1/4 lb. for air blowers
	105010	¼ lb.	1" S x 1¼" Spg	3 ¾"	White	20	5.0	41CV	Rated@ 200 PSI
	105020	¼ lb.	1½" S x 2" Spg	5 ½"	White	12	7.4	41CV	static pressure @ 72°F
	105520	5 lb.	1½" S x 2" Spg	5 ½"	White	12	8.0	41CV	

Clear Spa Check Valve 	1050C10	¼ lb.	1" S x 1¼" Spg	3 ¾"	Clear	20	5.0	41CV	Clear PVC,
	1050C20	¼ lb.	1½" S x 2" Spg	5 ½"	Clear	12	7.4	41CV	1/4 lb. for air blowers
	1050C20-05	½ lb.	1½" S x 2" Spg	5 ½"	Clear	12	7.4	41CV	Rated@ 200 PSI
	1050C20-10	10 lb.	1½" S x 2" Spg	5 ½"	Clear	12	7.4	41CV	static pressure @ 72°F
	1050C20-12	12 lb.	1½" S x 2" Spg	5 ½"	Clear	12	7.4	41CV	
	1050C20-15	15 lb.	1½" S x 2" Spg	5 ½"	Clear	12	7.4	41CV	
	1052C20	2 lb.	1½" S x 2" Spg	5 ½"	Clear	12	7.5	41CV	
	1055C20	5 lb.	1½" S x 2" Spg	5 ½"	Clear	12	8.0	41CV	

Clear Compact 	S1050C20	¼ lb.	1½" S x 2" Spg	4"	Clear	12	6	41CV	Clear PVC,
	S1050C20-05	½ lb.	1½" S x 2" Spg	4"	Clear	12	6	41CV	1/4 lb. for air blowers
	S1052C20	2 lb.	1½" S x 2" Spg	4"	Clear	12	6	41CV	Rated@ 200 PSI static pressure @ 72°F

ADJUSTABLE SPRING CHECK VALVES — SERIES 1200, 1700

Rated @ 200 PSI Static Pressure @ 72°F

	Part No.	IPS Size & Connection	Spring Tension	Body Length	Color	Pkg. Qty.	Case (lbs.)	Product Class	Specifications
White PVC FPT x FPT  Factory Set at 5 lb.	1205-05	½"	2 - 5 lb.	4 ⅞"	White	20	4.5	41CV	Rated @ 200 PSI
	1205-07	¾"	2½ - 5 lb.	4 ⅞"	White	20	4.5	41CV	static pressure @ 72°F
	1205-10	1"	4 ⅞ - 17 lb.	5 ¼"	White	20	8.5	41CV	Adjusting nut 1½ turn = 1 lb. force.
	1205-12	1¼"	4 - 50 lb.	6 ¾"	White	15	12.5	41CV	
	1205-15	1½"	3½ - 50 lb.	6 ¾"	White	15	13.5	41CV	NSF/ANSI 61+372
	1205-20	2"	1¼ - 14 ½ lb.	9 ¾"	White	10	14.5	41CV	Except: 1205V07
	1203-05	½"	3 lb.	4 ⅞"	White	20	4.5	41CV	
	1205-07-20	¾"	20 lb.	4 ⅞"	White	20	4.5	41CV	
	1205V07	¾" w/ VITON	5 lb.	4 ⅞"	White	20	4.5	41CV	

White PVC SxS 	1225-07	¾"	2½ - 5 lb.	4 ⅞"	White	20	4.5	41CV	Rated @ 200 PSI
	1225-10	1"	4¼ - 17 lb.	5 ¼"	White	20	8.5	41CV	static pressure @ 72°F
	1225-15	1½"	3½ - 50 lb.	6 ¾"	White	15	13.5	41CV	Adjusting nut 1½ turn = 1 lb. force.
	1228V15	1½"	30 lb.	6 ¾" w/ VITON	White	15	12.5	41CV	NSF/ANSI 61+372
									Except: 1228V15

	Part No.	Spring Tension	IPS Size	Body Length	Color	Pkg. Qty.	Case (lbs.)	Product Class	Specifications
White PVC FPT x MPT 	1235-05	2 - 4½ lb.	½"	4 ¼"	White	20	4.5	41CV	PVC
	1235-07	2½ - 5 lb.	¾"	4 ½"	White	20	4.5	41CV	Adjusting nut 1½
	1235-10	4¼ - 17 lb.	1"	5¼"	White	20	8.5	41CV	turn = 1 lb. force.
	1235-05-30	30 lb.	½"	4 ½"	White	20	4.5	41CV	NSF/ANSI 61+372
Factory Set at 5 lb.									
White PVC True Union 	1750-20	1 - 14 lb.	2"	9¾"	White	10	19.0	41CV	PVC
	1753-20	15 - 30 lb.	2"	9¾"	White	10	19.0	41CV	Adjusting nut 1½ turn = 1 lb. force. NSF/ANSI 61+372
Factory Set at 5 lb.									
Vacuum Relief Valve 	1171V57	½ lb.	½" S x ¾" MPT	4 ½"	Black	20	19.0	41CV	Adjusting nut 1½ turn = 1 lb. force Polypropylene w/cap and Viton Seals Not yet rated
Factory Set at ½ lb.									

ADJUSTABLE IN-LINE SPRING CHECK VALVE

	Part No.	Ref No.	Description	Pkg. Qty.	Product Class	Specifications
Inline Adjustable   	CV-0500-FF	1100-05	½" ADJ CHECK VALVE - FF	100	41CV	Preset @ approx. 5 lb with
	CV-0500-FM		½" ADJ CHECK VALVE - FM	100	41CV	EPDM Seal
	CV-0500-MF	1101-05	½" ADJ CHECK VALVE - MF	100	41CV	Adjusting nut 1½ turn = 1
	CV-0575-FM		½" x ¾" ADJ CHECK VALVE - FM	100	41CV	lb. force.
	CV-0750-FF	1100-07	¾" ADJ CHECK VALVE - FF	60	41CV	
	CV-0750-FM	1102-07	¾" ADJ CHECK VALVE - FM	60	41CV	
	CV-0750-MF	1101-07	¾" ADJ CHECK VALVE - MF	60	41CV	
	CV-1000-FF	1100-10	1" ADJ CHECK VALVE - FF	40	41CV	
	CV-1000-FM		1" ADJ CHECK VALVE - FM	40	41CV	
	CV-1000-MF		1" ADJ CHECK VALVE - MF	40	41CV	
	WCV-0750-MF		¾" MIPT x FIPT, White	60	41CV	
	WCV-1000-MF		1" MIPT x FIPT, White	40	41CV	
	UCV-0500-FF		½" UVR ADJ CHECK VALVE - FF	100	41CV	
	UCV-0500-MF		½" UVR ADJ. CHECK VALVE - MF	100	41CV	
	UCV-0750-FF		¾" UVR ADJ CHECK VALVE - FF	60	41CV	
	UCV-0750-MF		¾" UVR ADJ CHECK VALVE - MF	60	41CV	
	UCV-1000-FF		1" UVR ADJ CHECK VALVE - FF	40	41CV	

BREAKAWAY COUPLING VALVES

	Part No.	Spring Tension	IPS Size & Connection	Color	Pkg. Qty.	Case (lbs.)	Product Class	Specifications
Flo-Check Breakaway Coupling — Cal Trans Orange	1010-05-O	—	½" FPT x ½" FPT	Orange	30	3	41CV	Rated @ 150 PSI
	1010-07-O	—	¾" FPT x ¾" FPT	Orange	25	4	41CV	static pressure @ 72°F
	To be used on galvanized or iron pipe only.							

SWING CHECK VALVES



SWING CHECK VALVES – SERIES 1500

Rated @ 125 PSI Static Pressure @ 72°F

	Part No.	Ref No.	IPS Size & Connection	Body Length	Color	Pkg. Qty.	Case (lbs.)	Product Class	Specifications
White PVC Compression 	1500-12	KSC-1250-C	1¼" UC x UC	7½"	White	12	5.6	41CV	NSF/ANSI 61+372
	1500-15	KSC-1500-C	1½" UC x UC	7½"	White	12	6.3	41CV	
	1500-20	KSC-2000-C	2" UC x UC	9¾"	White	12	16.0	41CV	
	1500-30	KSC-3000-C	3" UC x UC	14"	White	2	10.0	41CV	
Clear PVC Compression 	1500C15	KSCC-1500-C	1½" UC x UC	7½"	Clear	12	6.3	41CV	Clear PVC
	1500C20	KSCC-2000-C	2" UC x UC	9¾"	Clear	12	16.0	41CV	
White PVC Threaded 	1520-05F	KSC-0500-T	½" FPT x FPT	3½"	White	20	4.0	41CV	PVC NSF/ANSI 61+372
	1520-07F	KSC-0750-T	¾" FPT x FPT	3½"	White	25	5.0	41CV	
	1520-10F	KSC-1000-T	1" FPT x FPT	5⅞"	White	25	10.0	41CV	
	1520-12F	KSC-1250-T	1¼" FPT x FPT	5¼"	White	12	6.9	41CV	
	1520-15F	KSC-1500-T	1½" FPT x FPT	5 ¾"	White	12	7.0	41CV	
	1520-20F	KSC-2000-T	2" FPT x FPT	6"	White	12	13.0	41CV	
	1520-20ST		2" FPT x S	6"	White	12	13.0	41CV	
White PVC S x S 	1520-05	KSC-0500-S	½" S x S	3½"	White	20	4.0	41CV	PVC NSF/ANSI 61+372 Except: 1520V20
	1520-07	KSC-0750-S	¾" S x S	3½"	White	25	5.0	41CV	
	1520-10	KSC-1000-S	1" S x S	5⅞"	White	25	10.0	41CV	
	1520-12	KSC-1250-S	1¼" S x S	5¼"	White	12	6.9	41CV	
	1520-15	KSC-1500-S	1½" S x S	5 ¾"	White	12	7.0	41CV	
	1520-20	KSC-2000-S	2" S x S	6"	White	12	13.0	41CV	
	1520-30	KSC-3000-S	3" S x S	9"	White	4	11.0	41CV	
	1520-40	KSC-4000-S	4" S x S	9½"	White	1	3.2	41CV	
	1520V20		2" S x S w/Viton seal	6"	White	12	13.0	41CV	
CPVC 	1520H10		1" S x S	5⅞"	Gray	25	10	41CV	CPVC
	1520H15		1½" S x S	5¾"	Gray	12	7	41CV	
	1520H20		2" S x S	6"	Gray	12	13	41CV	
	1520H30		3" S x S	9"	Gray	4	11	41CV	
	1520H40		4" S x S	9½"	Gray	1	3.2	41CV	
Clear PVC Threaded 	1520C05F	KSCC-0500-T	½" FPT x FPT	3½"	Clear	20	4.0	41CV	Clear PVC NSF/ANSI 61+372
	1520C07F	KSCC-0750-T	¾" FPT x FPT	3½"	Clear	25	5.0	41CV	
	1520C10F	KSCC-1000-T	1" FPT x FPT	5⅞"	Clear	25	10.0	41CV	
	1520C15F	KSCC-1500-T	1½" FPT x FPT	5¾"	Clear	12	7.0	41CV	
	1520C20F	KSCC-2000-T	2" FPT x FPT	6"	Clear	12	13.0	41CV	
Clear PVC S x S 	1520C05	KSCC-0500-S	½" S x S	3½"	Clear	20	4.0	41CV	Clear PVC NSF/ANSI 61+372
	1520C07	KSCC-0750-S	¾" S x S	3½"	Clear	25	5.0	41CV	
	1520C10	KSCC-1000-S	1" S x S	5⅞"	Clear	25	10.0	41CV	
	1520C12	KSCC-1250-S	1¼" S x S	5¼"	Clear	12	6.9	41CV	
	1520C15	KSCC-1500-S	1½" S x S	5 ¾"	Clear	12	7.0	41CV	
	1520C20	KSCC-2000-S	2" S x S	6"	Clear	12	13.0	41CV	
	1520C30	KSCC-3000-S	3" S x S	9"	Clear	4	11.0	41CV	
	1520C40	KSCC-4000-S	4" S x S	9½"	Clear	1	3.2	41CV	
	1520C15V		1½" S x S w/ Viton seal	5¾"	Clear	12	7.0	41CV	
	1520C20V		2" S x S w/ Viton seal	6"	Clear	12	13.0	41CV	

SWING CHECK VALVES - SERIES 1700

Rated @ 125 PSI Static Pressure @ 72°F

	Part No.	Ref. No.	IPS Size & Connection	Body Length	Color	Pkg. Qty.	Case (lbs.)	Product Class	Specifications
White PVC True Union 	1720-07		¾" U x U	5½"	White	20	9.0	41CV	PVC
	1720-10		1" U x U	6¾"	White	20	14.5	41CV	NSF/ANSI 61+372
	1720-15	KSC-1500-SU	1½" U x U	8"	White	12	13.5	41CV	
	1720-20	KSC-2000-SU	2" U x U	9½"	White	12	23.7	41CV	
	1720-30	KSC-3000-SU	3" U x U	12½"	White	6	33.5	41CV	

Clear PVC True Union 	1720C07	KSCC-0750-SU	¾" U x U	5½"	Clear	20	9.0	41CV	PVC
	1720C10	KSCC-1000-SU	1" U x U	6¾"	Clear	20	14.5	41CV	Clearbody with white nuts and tailpieces
	1720C15	KSCC-1500-SU	1½" U x U	8"	Clear	12	13.5	41CV	NSF/ANSI 61+372
	1720C20	KSCC-2000-SU	2" U x U	9½"	Clear	12	23.7	41CV	
	1720C30	KSCC-3000-SU	3" U x U	12½"	Clear	6	33.5	41CV	

	Part No.	Description	Pkg. Qty.	Product Class	Specifications
PVC Low Profile Swing Check Valve 	KSL-0750-S	¾" IPS HUB x IPS HUB Lo-Profile Swing Check Valve	18	41CV	Rated @ 150 PSI Static Pressure @ 72°F
	KSL-1000-S	1" IPS HUB x IPS HUB Lo-Profile Swing Check Valve	18	41CV	NSF/ANSI 61+372
	KSL-1250-S	1 1/4" IPS HUB x IPS HUB Lo-Profile Swing Check Valve	12	41CV	
	KSL-1500-S	1 1/2" IPS HUB x IPS HUB Lo-Profile Swing Check Valve	12	41CV	
	KSL-2000-S	2" IPS HUB x IPS HUB Lo-Profile Swing Check Valve	8	41CV	

SWING CHECK VALVES WITH SPRING ASSIST

Rated @ 125 PSI Static Pressure @ 72°F

	Part No.	Spring Tension	IPS Size & Connection	Body Length	Color	Pkg. Qty.	Case (lbs.)	Product Class	Specifications
Spring Loaded Swing Check Valve 	1780-20	½ lb.	2" UxU	9¾"	White	12	23.7	41CV	NSF/ANSI 61+372 PVC

SUMP PUMP VALVES / CHECKMATE

Rated @ 125 PSI Static Pressure @ 72°F

	Part No.	Ref. No.	IPS Size & Connection	Body Length	Check Valve Color	Pkg. Qty.	Case (lbs.)	Product Class	Specifications
Sump Pump Valve 	1400-15		1¼" or 1½" UC	5¼"	White	12	7.0	41CV	Buna "N" Gaskets are included in both 1¼" and 1½" size applications.
Checkmate 	2200-15	BCX-1500-S	1½" U x S	8"	White	12	20.8	41BV	
	2200-15UC		1½" UC x UC	10¾"	White	12	25.9	41BV	
	2200-15TU		1½" U x U	10½"	White	12	25	41BV	
	2200-20	BCX-2000-S	2" U x S	9¾"	White	12	30	41BV	
	2200C20TU		2" U x U	12¾"	Clear	12	36.2	41BV	
	2200-20UC		2" UC x UC	12 5/16"	White	12	37.5	41BV	
	2200-20TU		2" U x U	12¾"	White	12	36.2	41BV	

POOL DIVERTER VALVE



	Part No.	IPS Size & Connection	Body Length	Color	Pkg. Qty.	Case (lbs.)	Product Class	Specifications
CPVC Three-Way Diverter Valve 	1930-15	1½"		Tan	1	16.8	41PV	Rated @ 125
	1930-20	2" S & 2½" Spg		Tan	1	19.4	41PV	PSI Static Pressure @ 160°F

PVC Single Union Serviceable 	1350-15	1½" S x S	5½"	White	12	12.0	41BV	Rated @ 150
	1350-20	2" S x S	6"	White	6	6.0	41BV	PSI Static
	1351-15	1½" FPT x FPT	5½"	White	12	12.0	41BV	Pressure @
	1351-20	2" FPT x FPT	6"	White	6	6.0	41BV	72°F

	Part No.	Description	Color	Pkg Qty.	Product Class	Specifications
PVC Single Union Serviceable 	WSU-1520-S	1 1/2"+2" x 1 1/2" +2" IPS HUB and SPIGOT	White	8	42LT	Rated @ 150 PSI Static Pressure @ 72°F

MIP (MOLDED-IN-PLACE) BALL VALVES

Rated @ 150 PSI Static Pressure @ 72°F

	Part No.	IPS Size & Connection	Body Length	Color	Pkg. Qty.	Case (lbs.)	Product Class
MIP Non-Serviceable WHITE  ½" - 2"  2 ½" - 4"	E1310-05	½" S x S	3¼"	White	36	6.5	41MV
	E1310-07	¾" S x S	3¾"	White	18	5.9	41MV
	E1310-10	1" S x S	4¼"	White	25	12.4	41MV
	E1310-12	1¼" S x S	4½"	White	12	7.6	41MV
	E1310-15	1½" S x S	5¼"	White	12	11.6	41MV
	E1310-20	2" S x S	5¾"	White	6	9.6	41MV
	E1310-25	2½" S x S	7"	White	6	15	41MV
	E1310-30	3" S x S	8½"	White	2	4	41MV
	E1310-40	4" S x S	9"	White	1	3	41MV
	E1310-60	6" S x S	13"	White	1	5	41MV
	E1320-05	½" FPT x FPT	3¼"	White	36	6.7	41MV
	E1320-07	¾" FPT x FPT	3¾"	White	18	6.1	41MV
	E1320-10	1" FPT x FPT	4¼"	White	25	13.0	41MV
	E1320-12	1¼" FPT x FPT	4¼"	White	12	8.0	41MV
	E1320-15	1½" FPT x FPT	5½"	White	12	12.0	41MV
	E1320-20	2" FPT x FPT	5¾"	White	6	10.0	41MV
	E1320-25	2½" FPT x FPT	7"	White	6	15	41MV
	E1320-30	3" FPT x FPT	8½"	White	2	4	41MV
	E1320-40	4" FPT x FPT	9"	White	1	3	41MV

MIP Non-Serviceable GRAY 	E1610-05	½" S x S	3¼"	Gray	36	6.5	41MV
	E1610-07	¾" S x S	3¾"	Gray	18	5.9	41MV
	E1610-10	1" S x S	4¼"	Gray	25	12.4	41MV
	E1610-12	1¼" S x S	4½"	Gray	12	7.6	41MV
	E1610-15	1½" S x S	5¼"	Gray	12	11.6	41MV
	E1610-20	2" S x S	5¾"	Gray	6	9.6	41MV
	E1620-05	½" FPT x FPT	3¼"	Gray	36	6.7	41MV
	E1620-07	¾" FPT x FPT	3¾"	Gray	18	6.1	41MV
	E1620-10	1" FPT x FPT	4¼"	Gray	25	13.0	41MV
	E1620-12	1¼" FPT x FPT	4¼"	Gray	12	8.0	41MV
	E1620-15	1½" FPT x FPT	5½"	Gray	12	12.0	41MV
	E1620-20	2" FPT x FPT	5¾"	Gray	6	10.0	41MV