INDUSTRIAL INTERCHANGE

- Meets ISO 6150-B
- ANSI (NFPA) T3.20.14-1990
- The SV Series Meets ISO 4414

Plugs	Plugs
R	
E-FE	

Standard



Valve Core

Ball Check



Manual

Industrial



Automatic

Complies with



Manual



SV3003

SV3203

SV3103

SV3303

SV3603

SV3703

Safety

				do ob					
	Size	Cat. No.	Cat. No.	Cat. No.	Cat. No.	Cat. No.	Cat. No.	Cat. No.	(
	Female Thread					BL optional [4]	SL optional [5]		(max)
	1/8 FPT	13-3				2803	FM2803	SG2803	
	1/8 FPT [Brass]	13-3B				_			
	1/8 FPT [303 Stainless]	13-3S/S				2803S/S	_	_	
	1/4 FPT	11-3				3003	FM3003	SG3003	
	1/4 FPT [Brass]	11-3B	_	_	_	_			
Į	1/4 FPT [303 Stainless]	11-3S/S				3003S/S	_	_	
	3/8 FPT	15-3				3203	FM3203	SG3203	
	3/8 FPT [303 Stainless]	-				3203S/S	-	-	
	Male Thread		Free Swivel Under Pressure [3]	Ball Check Plug [1]	Valve Core Plug [2]				
	1/8 MPT	12-3	12S-3			2903	FM2903	SG2903	
	1/8 MPT [Brass]	12-3B	_	_	_	_	_	_	
	1/8 MPT [303 Stainless]	12-3S/S				2903S/S			
	1/4 MPT	10-3	10S-3	10-3G	10-3D	3103	FM3103	SG3103	
	1/4 MPT [Spring Loaded]	-	-	10-3GS	-	-	-	-	
	1/4 MPT [Brass]	10-3B	_	10-3GB	10-3DB	-	_	_	
	1/4 MPT [303 Stainless]	10-3S/S		10-3GS/S		3103S/S			
	3/8 MPT	14-3	14S-3	14-3GB	_	3303	FM3303	SG3303	
	3/8 MPT [Brass]	14-3B	_	_		_	_	_	
	3/8 MPT [303 Stainless]	-				3303S/S			
	Hose Stem (Requires Hose Clamps)								
	1/4 I.D.	16-3				3603	FM3603	SG3603	
	1/4 I.D. [Brass]	16-3B				_	_	_	
	1/4 I.D. [303 Stainless]	-				3603S/S		_	
	⁵ /16 I.D.	165-3	-	_	_	3653	FM3653		
	3/8 I.D.	17-3				3703	FM3703	SG3703	
	3/8 I.D. [Brass]	17-3B				_	_	_	
	3/8 I.D. [303 Stainless]	_				3703S/S			
	Push-On Hose Stem								
	1/4 I.D.	51-3	_	_	_	1513	FM1513	SG1513	
	3/8 I.D.	71-3				1713	FM1713	SG1713	
	Reusable Hose Clamp ID x OD							[1] Ball check plugs elimi disconnect by checkin	ng the r
	1/4 x 1/2	PB3-3				SB3-3	FMSB3-3	downstream exhaust a	
	1/4 x 1/2 [Brass]	PB3-3B				-	_	[2] Sockets with modified val	
	1/4 x 1/2 [303 Stainless]	PB3-3S/S				SB3-3S/S		for use with valve core plu	ugs. Sut
ļ	1/4 x ⁹ /16	PB5-3				SB5-3	FMSB5-3	Cat. No.	
	1/4 x 9/16 [Brass]	PB5-3B	_	_	_	_	_	[3] Swivel Plugs – Eliminates applications such as blow	
ļ	1/4 x 5/8	PB7-3				SB7-3	FMSB7-3	[4] BL – Locks manual socke	
	1/4 x 5/8 [Brass]	PB7-3B				-	_	disconnect. To order, pref	
	1/4 x 5/8 [303 Stainless]	PB7-3S/S				SB7-3S/S	5110B0 0	[5] SL – Locks automatic so	
ļ	1/4 x 11/16	PB9-3				SB9-3	FMSB9-3	disconnect. To order, cha	
ļ	1/4 x 11/16 [Brass]	PB9-3B				-	-		J

Profile drawings available at www.couplers.com

PC5-3

PC7-3

PD7-3

PD9-3

PD11-3

PD13-3

• See Page 68 for Specifications, Performance Data, Full Size Templates, and Optional Seal Compounds

- hose whip at rapid flow of
- are recommended Suffix-D to socket
- e twist on end drop s, air tools, etc.
- inst accidental to socket number.
- gainst accidental M prefix to SL.





Dust Caps, Plugs 3PDC

Dust Caps, Sockets 3SDC

⁵/16 x ⁹/16

5/16 x 5/8

3/8 x 5/8

3/8 x 3/4

3/8 x 13/16

3/8 x 11/16

SC5-3

SC7-3

SD7-3

SD9-3

SD11-3

SD13-3

FMSC5-3

FMSC7-3

FMSD7-3

FMSD9-3

FMSD11-3

FMSD13-3