



Compressed Air Blow Guns

**Safety
Controlled-Flow**

**OSHA
Compliant**

	Lever Operated Handy-Air® Blow Gun	Button Operated Handy-Air® Blow Gun	Nickel Plated Handy-Air® Blow Gun
			
	Cat. No.	Cat. No.	Cat. No.
Pressed – Safety Tip	BG2L-30STP	BG2-30STP	–
Threaded – Safety Tip	BG2L-30STT	BG2-30STT	BG2L-STT
Pressed – Standard Tip	BG2L-30P	BG2-30P	–
Threaded – Standard Tip	BG2L-30T	BG2-30T	–

Inlet Pressure: 150 PSIG maximum

Temperature: +32° to +180° F

Flow Safety Tip: 19.8CFM@100 PSIG

Flow Standard Tip: 9.3 CFM@100 PSIG

Body: Die cast Zinc:

Seal: Buna-N:

Inlet: 1/4" FPT

Safety Tip - Standard Tip – Handy-Air® models are available with either the standard or ST safety tip, each of which may be ordered pressed or threaded to the gun. The pressed tip is not removable and resists tampering. The threaded tip has a 1/8" NPT male thread. The ST safety tip provides a conical shield of air which encircles blown chips or particles directing them away from the operator.

Non-Regulated Blow Guns

Standard model blow guns are available for those installations not requiring reduced pressure. These two die cast models are not OSHA compliant.

Cat. No. BG2 (Button Operated)

Cat. No. BG2L (Lever Operated)

**Safety
Controlled- Flow**

**OSHA
Compliant**

1/4" FPT Inlet

	Pistol Grip Blow Gun
	
	Cat. No.
Pressed Safety Tip	PG2P
Threaded Safety Tip	PG2T

Blowgun Accessories		
Item	Cat. No.	Description
12" Extension	EX12	
		<ul style="list-style-type: none"> Permanent extension. Employs same tip as gun. Dynamic and static pressures same as gun installed on.
10" Extension	EX10DH	
		<ul style="list-style-type: none"> Removable extension, push on, twist off. Durable tubing with female tapered fitting. Fits snugly on standard or safety tip.
Rubber Tip	EX2RT	 <ul style="list-style-type: none"> Protects delicate parts from damage Blowguns with rubber tip will not comply with OSHA requirements. Installs on all threaded blowguns with 1/8" NPT
Standard Safety Tip	EX2	 <ul style="list-style-type: none"> High flow safety nozzle for general dusting and chip removal Installs on all threaded blowguns with 1/8" NPT
Safety Air Screen Tip	EX2ST	 <ul style="list-style-type: none"> Air screen nozzle reduces chip fly back Installs on all threaded blowguns with 1/8" NPT

Inlet Pressure: 150 PSIG maximum

Temperature: +32° to +120° F

Flow: 19.8CFM@100 PSIG

Body: Nylon 6

Seal: Buna-N

Features

- OSHA Compliant
- Pistol grip design is more comfortable to operate
- Trigger/Valve design allows for variable output
- Safety tip standard
- Trigger serves as a convenient hanging hook
- Color, safety yellow