


MALLEABLE IRON STRAIGHT COUPLING CLASS 300

NPS	Length of Coupling A (min)	Outside Dia. of Band B (min)	Length of Threads C (min)	Take Out
1/4	1.37	0.93	0.43	0.28
3/8	1.62	1.12	0.47	0.40
1/2	1.87	1.34	0.57	0.40
3/4	2.12	1.63	0.64	0.51
1	2.37	1.95	0.75	0.50
1 1/4	2.87	2.39	0.84	0.73
1 1/2	2.87	2.68	0.87	0.71
2	3.62	3.28	1.00	1.05
2 1/2	—	—	—	—
3	—	—	—	—



MALLEABLE IRON REDUCING COUPLING CLASS 300

NPS	Length of Coupling A	Outside Dia. of Band Small End B (min)	Outside Dia. of Band Large End B2 (min)	Length of Threads Small End C (min)	Length of Threads Large End C2 (min)	Take Out	Take Out
3/8 x 1/4	1.44	0.93	1.20	0.43	0.47	0.31	0.32
1/2 x 3/8	1.69	1.12	1.34	0.47	0.57	0.31	0.44
1/2 x 1/4	1.69	0.93	1.34	0.43	0.57	0.31	0.44
3/4 x 1/2	1.75	1.34	1.63	0.57	0.64	0.33	0.34
3/4 x 3/8	—	—	—	—	—	—	—
3/4 x 1/4	—	—	—	—	—	—	—
1 x 3/4	2.00	1.63	1.95	0.64	0.75	0.32	0.45
1 x 1/2	2.00	1.34	1.95	0.57	0.75	0.32	0.47
1 x 3/8	—	—	—	—	—	—	—
1 x 1/4	—	—	—	—	—	—	—
1 1/4 x 1	2.38	1.95	2.39	0.75	0.84	0.48	0.51
1 1/4 x 3/4	2.38	1.63	2.39	0.64	0.84	0.48	0.64
1 1/4 x 1/2	—	—	—	—	—	—	—
1 1/2 x 1 1/4	2.69	2.39	2.68	0.84	0.87	0.62	0.64
1 1/2 x 1	2.69	1.95	2.68	0.75	0.87	0.62	0.66
1 1/2 x 3/4	2.69	1.63	2.68	0.64	0.87	0.62	0.80
1 1/2 x 1/2	—	—	—	—	—	—	—
2 x 1 1/2	3.19	2.68	3.28	0.87	1.00	0.84	0.87
2 x 1 1/4	3.19	2.39	3.28	0.84	1.00	0.84	0.89
2 x 1	3.19	1.95	3.28	0.75	1.00	0.84	0.91
2 x 3/4	—	—	—	—	—	—	—
2 x 1/2	—	—	—	—	—	—	—
2 1/2 x 2	—	—	—	—	—	—	—
2 1/2 x 1 1/2	—	—	—	—	—	—	—
3 x 2 1/2	—	—	—	—	—	—	—
3 x 2	—	—	—	—	—	—	—
3 x 1 1/2	—	—	—	—	—	—	—
4 x 3	—	—	—	—	—	—	—
4 x 2	—	—	—	—	—	—	—

