


PRODUCT RANGE - BUSHING

aquatherm BUSHING

Female to male for use with standard fitting. Female side is identified by a socket-fitting structure, male side is identified with a beveled edge. Appearance of bushing will vary by dimension.



Part no.	Dimension (ND — OD) (M-F)	d	d1	l	z	D	Weight
		[in]	[in]	[in]	[in]	[in]	[lb]
0111112	¾ to ½" — 25 to 20 mm	1.16	0.79	1.52	0.94	0.98	0.03
0111114	1" to ½" — 32 to 20 mm	1.26	0.79	1.48	0.91	1.16	0.03
0111116	1" to ¾" — 32 to 25 mm	1.34	0.98	1.50	0.87	1.26	0.03
0111118	1 ¼" to ½" — 40 to 20 mm	1.57	0.79	1.77	1.20	1.16	0.05
0111120	1 ¼" to ¾" — 40 to 25 mm	1.57	0.98	1.97	1.34	1.34	0.06
0111122	1 ¼" to 1" — 40 to 32 mm	1.69	1.26	1.97	1.26	1.57	0.07
0111124	1 ½" to ½" — 50 to 20 mm	1.97	0.79	2.17	1.59	1.16	0.10
0111126	1 ½" to ¾" — 50 to 25 mm	1.97	0.98	2.17	1.54	1.34	0.10
0111128	1 ½" to 1" — 50 to 32 mm	1.97	1.26	2.13	1.42	1.69	0.11
0111130	1 ½" to 1 ¼" — 50 to 40 mm	2.05	1.57	2.07	1.26	1.97	0.12
0111131	2" to ½" — 63 to 20 mm	2.48	0.79	2.56	1.99	1.16	0.16
0111132	2" to ¾" — 63 to 25 mm	2.48	0.98	2.56	1.93	1.34	0.16
0111134	2" to 1" — 63 to 32 mm	2.48	1.26	2.44	1.73	1.69	0.18
0111136	2" to 1 ¼" — 63 to 40 mm	2.48	1.57	2.56	1.75	2.05	0.23
0111138	2" to 1 ½" — 63 to 50 mm	2.68	1.97	2.50	1.57	2.48	0.25
0111143	2 ½" to ½" — 75 to 20 mm	2.95	0.79	2.58	2.01	1.36	0.24
0111144	2 ½" to ¾" — 75 to 25 mm	2.95	0.98	2.58	1.95	1.36	0.24
0111145	2 ½" to 1" — 75 to 32 mm	2.95	1.26	2.74	2.03	2.05	0.31
0111139	2 ½" to 1 ¼" — 75 to 40 mm	2.95	1.57	2.74	1.93	2.05	0.29
0111140	2 ½" to 1 ½" — 75 to 50 mm	2.95	1.97	2.48	1.56	2.68	0.31
0111142	2 ½" to 2" — 75 to 63 mm	3.31	2.48	2.80	1.71	2.95	0.38
0111151	3" to 1 ½" — 90 to 50 mm	3.54	1.97	2.95	2.03	2.68	0.43
0111152	3" to 2" — 90 to 63 mm	3.54	2.48	3.07	1.99	3.31	0.49
0111153	3" to 2 ½" — 90 to 75 mm	3.94	2.95	3.21	2.03	3.54	0.60
0111155	3 ½" to 2" — 110 to 63 mm	4.33	2.48	3.39	2.30	3.31	0.79
0111157	3 ½" to 2 ½" — 110 to 75 mm	4.33	2.95	3.50	2.32	3.94	0.84
0111159	3 ½" to 3" — 110 to 90 mm	4.72	3.54	3.90	2.60	4.33	1.10
0111161	4" to 2 ½" — 125 to 75 mm	4.92	2.95	3.98	2.80	3.94	1.14
0111163	4" to 3" — 125 to 90 mm	4.92	3.54	3.90	2.60	4.72	1.30
0111165	4" to 3 ½" — 125 to 110 mm	5.79	4.33	4.41	2.95	4.92	1.83