



PRODUCT RANGE - 45(s) MOLDED

aquatherm STREET 45° female/male



Part no.	Dimension (ND — OD)	d	z	l	D	l1	z1	Weight
		[in]	[in]	[in]	[in]	[in]	[in]	[lb]
0112708	½" — 20 mm	0.79	0.20	0.77	1.16	0.77	0.35	0.03
0112710	¾" — 25 mm	0.98	0.24	0.87	1.34	0.87	0.33	0.04
0112712	1" — 32 mm	1.26	0.30	1.00	1.69	1.12	0.45	0.08
0112714	1 ¼" — 40 mm	1.57	0.37	1.18	2.05	1.20	0.53	0.13

aquatherm blue pipe® ELBOW 45° SD (SEGMENTED, BUTT-FUSION)



SDR	Part no.	Dimension (ND — OD)	d	z	Weight
			[in]	[in, +0.25/-0.0]	[lb]
17.6	7412530 ^a	6" — 160 mm	6.30	7.44	4.00
	7412534 ^a	8" — 200 mm	7.87	9.94	4.25
	7412538	10" — 250 mm	9.84	6.25	8.00
	7412542	12" — 315 mm	12.4	7.50	15.0
	7412544	14" — 355 mm	14.0	8.75	22.0
	7412546	16" — 400 mm	15.8	10.0	31.0
	7412548	18" — 450 mm	17.7	11.3	44.0
	7412550	20" — 500 mm	19.7	12.5	60.0
	7412554	24" — 630 mm	24.8	15.0	114
11	7512530 ^a	6" — 160 mm	6.30	7.44	6.00
	7512534 ^a	8" — 200 mm	7.87	9.94	6.25
	7512538	10" — 250 mm	9.84	6.25	12.0
	7512542	12" — 315 mm	12.4	7.50	22.0
	7512544	14" — 355 mm	14.0	8.75	33.0
	7512546	16" — 400 mm	15.8	10.0	48.0
	7512548	18" — 450 mm	17.7	11.3	67.0
9	7212530	6" — 160 mm	6.30	7.44	6.71
	7212534	8" — 200 mm	7.87	9.94	14.0
	7212538	10" — 250 mm	9.84	6.25	13.7
	7212542	12" — 315 mm	12.4	7.50	26.1
	7212544	14" — 355 mm	14.0	8.75	38.7

^aMade with the Z-value of the ANSI B16.9 3D fittings with a larger Z-value.

UV Coated fittings available upon request. Contact your Aquatherm Regional Sales Manager for pricing and availability.