

Class 150 Bronze Gate Valves

Union Bonnet • Rising Stem • Solid Wedge

150 PSI/10.3 Bar Saturated Steam to 366° F/185° C
 300 PSI/20.7 Bar Non-Shock Cold Working Pressure

CONFORMS TO MSS SP-80

MATERIAL LIST

PART	SPECIFICATION
1. Handwheel Nut	300 Series Stainless Steel
2. Identification Plate	Aluminum
3. Handwheel	Malleable Iron ASTM A 47
4. Stem	Silicon Bronze ASTM B 371 Alloy C69400/C69430 or ASTM B 99 Alloy C65100
5. Packing Nut	Bronze ASTM B 62 or ASTM B 584 Alloy C84400 or Brass ASTM B 16
6. Packing Gland	Bronze ASTM B 62 or ASTM B 584 Alloy C84400 or Brass ASTM B 16
7. Packing	Aramid Fibers with Graphite
8. Bonnet	Bronze ASTM B 62
9. Union Nut	Bronze ASTM B 62
10. Body	Bronze ASTM B 62
11. Wedge	Bronze ASTM B 62

DIMENSIONS—WEIGHTS—QUANTITIES

Size		Dimensions						T-134		S-134		Master Ctn. Qty.
		A		B		C						
In.	mm.	In.	mm.	In.	mm.	In.	mm.	Lbs.	Kg.	Lbs.	Kg.	
1/4	8	1.96	50	4.81	122	x	x	1.08	0.49	x	x	50
3/8	10	1.96	50	4.81	122	0.79	20	1.12	0.51	1.02	0.46	50
1/2	15	2.31	59	4.81	122	0.76	19	1.12	0.51	1.06	0.48	40
3/4	20	2.51	64	5.81	148	0.98	25	1.70	0.77	1.54	0.70	30
1	25	2.92	74	7.09	180	1.13	29	2.38	1.08	2.26	1.03	20
1 1/4	32	3.20	81	8.13	206	1.18	30	3.73	1.69	3.56	1.61	10
1 1/2	40	3.33	85	9.81	249	1.29	33	4.67	2.12	4.46	2.02	10
2	50	3.44	87	11.56	294	1.31	33	7.77	3.53	7.14	3.24	6
2 1/2	65	4.35	110	14.31	364	1.81	46	12.70	5.77	12.30	5.58	4
3	80	5.31	135	16.50	419	1.97	50	18.74	8.51	17.13	7.78	2


x Not available this size.

 Dezincification
Resistant



T-134
Threaded



S-134
Solder



T-134
NPT x NPT



S-134
C x C

FREEZING WEATHER PRECAUTION: Subsequent to testing a piping system, valves should be left in an open position to allow complete drainage.

♦ For detailed Operating Pressure, refer to Pressure Temperature Chart on page 111.