

PVC Foam Core Pipe

PVC Schedule 40 DWV Pipe
(For Non-Pressure Applications)



PVC SCHEDULE 40 FOAM CORE (WHITE)			PLAIN END		ASTM F 891	
PART NO.	NOM. SIZE	UPC # 611942-	QTY. PER SKID	AVG. OD (IN.)	MIN. WALL (IN.)	WT. PER 100 FT. (LBS.)
PVC 4112	1½" x 10'	04178	1720	1.900	0.145	38.1
PVC 4112	1½" x 20'	04177	3440	1.900	0.145	38.1
PVC 4200	2" x 10'	04174	990	2.375	0.154	51.2
PVC 4200	2" x 20'	04173	1980	2.375	0.154	51.2
PVC 4300	3" x 10'	03934	1040	3.500	0.216	105.0
PVC 4300	3" x 20'	03935	920	3.500	0.216	105.0
PVC 4400	4" x 10'	03936	600	4.500	0.237	146.0
PVC 4400	4" x 20'	03937	1200	4.500	0.237	146.0
PVC 4600	6" x 10'	03938	280	6.625	0.280	247.0
PVC 4600	6" x 20'	03939	560	6.625	0.280	247.0
PVC 4800	8" x 20'	03941	360	8.625	0.322	371.0
PVC 4910	10" x 20'	03942	220	10.750	0.365	566.0
PVC 4912	12" x 20'	03943	120	12.750	0.406	755.0

PVC - DWV PIPE

PVC SCHEDULE 40 FOAM CORE (WHITE)			BELL-END			
PART NO.	NOM. SIZE	UPC # 611942-	QTY. PER SKID	AVG. OD (IN.)	MIN. WALL (IN.)	WT. PER 100 FT. (LBS.)
PVC 4300B	3" x 20'	04782	920	3.500	0.216	105.0
PVC 4400B	4" x 10'	04783	540	4.500	0.237	146.0
PVC 4400B	4" x 20'	04784	1080	4.500	0.237	146.0
PVC 4600B	6" x 20'	04786	480	6.625	0.280	247.0

NOTE: When ordering, please specify plain end or bell end.

NSF Listed. Meets All Requirements of
ASTM F 891.

NOTICE

NOT FOR PRESSURE

Do not use PVC / ABS cellular core (foam core) pipe for pressure applications. The use of cellular core pipe in pressure applications may result in system failure and property damage.

WARNING

Testing with or use of compressed air or gas in PVC / ABS / CPVC pipe or fittings can result in explosive failures and cause severe injury or death.

- NEVER test with or transport/store compressed air or gas in PVC / ABS / CPVC pipe or fittings.
- NEVER test PVC / ABS / CPVC pipe or fittings with compressed air or gas, or air over water boosters.
- ONLY use PVC / ABS / CPVC pipe for water or approved chemicals.
- Refer to warnings in PPFA User Bulletin 4-80 and ASTM D 1785.

